



# SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

**1776-10-1097**

## ALUJET Optima FDSK

Product group: Vapor barriers / vapor retarders - Roof membranes



ALUJET GmbH  
Ahornstraße 16  
82291 Mammendorf



### Product qualities:



*Köttner*  
Helmut Köttner  
Scientific Director  
Freiburg, 02 February 2026



Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## Contents

■ SHI Product Assessment 2024	1
■ QNG - Qualitätssiegel Nachhaltiges Gebäude	2
■ DGNB New Construction 2023	3
■ DGNB New Construction 2018	4
■ BNB-BN Neubau V2015	5
■ EU taxonomy	6
■ BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m <sup>3</sup> Formaldehyd ≤ 24 µg/m <sup>3</sup>	Indoor Air Quality Certified

**Valid until: 27 September 2028**



Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## ■ QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment



Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## **DGNB New Construction 2023**

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
<b>Verification:</b> SHI-Schadstoffgeprüft	

Criteria	Assessment
ENV1.1 Climate action and energy (*)	May positively contribute to the overall building score

Criteria	Assessment
ECO1.1 Life cycle cost (*)	May positively contribute to the overall building score

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment



Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## **BNB-BN Neubau V2015**

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment

Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
<b>Verification:</b> EMICODE EC1+ Zertifikat			

Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## **BREEAM DE Neubau 2018**

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment



Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC<sub>1</sub><sup>PLUS</sup> label, as the premium class, sets significantly stricter emission limits than the other label variants.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:

**ALUJET Optima FDSK**

SHI Product Passport no.:

**1776-10-1097**



## Legal notices

(\*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

---

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte>

---

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



## Publisher

Sentinel Holding Institut GmbH  
Bötzinger Str. 38  
79111 Freiburg im Breisgau  
Germany  
Tel.: +49 761 590 481-70  
info@sentinel-holding.eu  
www.sentinel-holding.eu

## ALUJET Optima FDSK

### Produkt- beschreibung

► Die ALUJET Optima FDSK ist eine vollflächig selbstklebende Dampfsperre und für den Einsatz im Bereich Trapezdach und Flachdach konzipiert. Sowohl die Vorgaben der DIN 4108-7 als auch der DIN 18234-1 und 2 werden erfüllt. Durch den Aluminiumverbund wurde eine Bahn geschaffen, die durch ihr geringes Gewicht, einer Breite von 1,50 m als auch einer hohen Reißfestigkeit die optimale Bahn für große Flächen ist.




Abb. 1: ALUJET Optima FDSK

Abb. 2: ALUJET Optima FDSK

### Vorteile

► Vollflächig selbstklebend; hohe Reißfestigkeit; hohe Deckbreite; schnelle Verarbeitung großer Flächen, da weniger Querstöße; E nach EN 13501-1; Heizwert <10.500 kJ/m<sup>2</sup>; dampfdicht (sd-Wert >1.500 m), brandlastreduziert.

### Einsatzgebiet

► Die ALUJET Optima FDSK ist für den Einsatz auf Flachdächern mit Trapezblech, OSB, glattem Holz bzw. Beton\* vorgesehen.

\*mit Bitumenvoranstrich

### Spezifikation

► Rollenbreite: 1.500 mm  
Rollenlänge: 50 m  
Rolleninhalt: 75 m<sup>2</sup>

### Technische Daten

Prüfung	Norm	Einheit	Wert
Flächengewicht	EN 1848-2	g / m <sup>2</sup>	138 ±7
Materialstärke inklusive Klebeausrüstung		mm	ca. 0,17
Brandklasse	EN 13501-1	---	E
Heizwert	DIN EN ISO 1716	kJ/m <sup>2</sup>	< 10.500
Verarbeitungstemperatur		°C	ab +5
Wasserdichtheit gegen Wasser in flüssiger Form	EN 1928	2 kPa	bestanden
Sd-Wert	EN 1931	m	≥ 1.500 m
Zugfestigkeit längs	EN12311-2	N / 50 mm	> 500
Zugfestigkeit quer	EN12311-2	N / 50 mm	> 500
Dehnung längs	EN12311-2	%	> 10
Dehnung quer	EN12311-2	%	> 10
Widerstand gegen Weiterreißen längs	EN12310-1	N	> 250
Widerstand gegen Weiterreißen quer	EN12310-1	N	> 250
Widerstand gegen Stoßbelastung	EN 12691	mm	>2000
Dauerhaftigkeit gegen künstliche Alterung	EN 1296 / EN 1928		bestanden
Dauerhaftigkeit gegen Alkalien	EB 1847 / EN 1928		bestanden
Widerstand gegen statische Belastung	EN 12730	kg	>20
Freibewitterung		Wochen	4
Notabdichtung/Behelfsdeckung		Wochen	4

- Verarbeitung** ► Die ALUJET Optima FDSK wird eingesetzt im Flachdachbereich auf Profilblechen, glattes Holz, OSB bzw. Beton\*. Bei Profilblechen ist zu berücksichtigen, dass die Bahn parallel zu den Obergurten verlegt wird. Quer- und Längsstöße sind mit einer Überlappung von mindestens 8 cm auszuführen. Nach dem Abziehen des Trennliners ist die ALUJET Optima FDSK auf den Obergurten anzudrücken. Durch die vollflächig selbstklebende Ausrüstung sind keine zusätzlichen Klebebänder für die Überlappungsverklebung notwendig. Beschädigte Stellen können direkt mit der ALUJET Optima FDSK beseitigt werden. Um Fehlklebungen zu vermeiden ist die ALUJET Optima FDSK ohne Zug- und Scherkräfte zu verlegen. Der Untergrund muss trocken / staubfrei und fettfrei sein.

Beim Einsatz als Notabdichtung/Behelfsdeckung ist eine Dachneigung von mindestens 2% notwendig. Die Notentwässerung/ausreichende Dachentwässerung muss eingeplant werden. Eine Not- und Behelfsabdichtung mit der ALUJET Optima FDSK ist gegebenenfalls mit dem Auftraggeber gesondert zu vereinbaren. Basis für die Verarbeitung der ALUJET Optima FDSK ist eine mechanische Befestigung bzw. die Verlegung unter Auflast.

\*mit Bitumenvoranstrich

- Lagerung** ► Ohne Einwirken von UV-Strahlung, da hierdurch die Eigenschaften des Materials dauerhaft reduziert werden könnten.

- DGNB** ► Das Produkt qualifiziert sich für den Einsatz in allen DGNB-Neubauprojekten bis zur höchsten Auszeichnungsstufe "Platin". Dies wird durch das unabhängige Sentinel Haus Institut bestätigt, welches das Produkt gemäß den Anforderungen des DGNB Steckbriefs ENV1.2 "Risiken für die lokale Umwelt" (Version 2023) geprüft hat. Aufgrund der sehr guten Produkteigenschaften hinsichtlich des Schadstoffgehalts sind für die DGNB-Zertifizierung keine zusätzlichen Nachweisdokumente erforderlich.

**Hinweise**



Unsere Gebrauchsanweisungen, Verarbeitungsrichtlinien, Produkt- oder Leistungsangaben und sonstigen technischen Aussagen sind nur allgemeine Richtlinien; sie beschreiben nur die Beschaffenheit unserer Produkte (Werteangaben / -ermittlung zum Produktionszeitpunkt) und Leistungen und stellen keine Garantie im Sinne des §443 BGB dar. Wegen der Vielfalt der Verwendungszwecke des einzelnen Produkts und der jeweiligen besonderen Gegebenheiten (z.B. Verarbeitungsparameter, Materialeigenschaften etc.) obliegt dem Anwender die eigene Erprobung; unsere kostenlose anwendungstechnische Beratung in Wort, Schrift und Versuch ist unverbindlicher Art.

**Lizenzerteilung zur Führung des EMICODE**

Lizenzierungs-Nummer: 17450/12.02.23

Für den Artikel ALUJET Optima FDSK  
der Firma ALUJET GmbH  
wird auf Antrag vom 25.09.2023

unter Bezugnahme auf die Einstufung gemäß den nach § 10 der GEV-Zeichensatzung festgelegten Richtlinien

namens der Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V. für den oben genannten Artikel nach § 5 Abs. 4 der GEV-Zeichensatzung die Lizenz zur Führung des GEV-Zeichens



erteilt. Damit erfüllt dieser Artikel die rückseitig aufgeführten Kriterien.  
Die Firma ist ordentliches Mitglied der GEV.



Der Geschäftsführer  
Gemeinschaft Emissionskontrollierte Verlegewerkstoffe,  
Klebstoffe und Bauprodukte e.V.  
Völklinger Straße 4 · D-40219 Düsseldorf

**OM240 27.09.2023**  
gültig bis 27.09.2028

## Hinweise zu den Voraussetzungen über die Vergabe der Lizenz für den EMICODE

Das gemäß vorseitiger Lizenz eingestufte Produkt hat nach der Satzung und den Richtlinien des Technischen Beirats der GEV u.a. den folgenden Kriterien zu genügen:

- Das Produkt entspricht allen gesetzlichen Bestimmungen, insbesondere denen des Chemikalienrechtes und seiner Verordnungen.
- Das Produkt ist nach der Definition der TRGS 610 lösemittelfrei, sofern es sich nicht um ein Oberflächenprodukt handelt. Soweit es einer Produktgruppe nach GISCODE zuzuordnen ist, wird diese angegeben.
- Für das Produkt wird ein Sicherheitsdatenblatt nach lokalem Recht in der jeweils aktuellen Fassung erstellt.
- Krebsverregende, erbgutverändernde oder fruchtschädigende Stoffe der Klassen 1A und 1B werden dem Produkt bei der Herstellung nicht zugesetzt.
- Die Prüfung des Produktes erfolgt nach der definierten „GEV-Prüfmethode“. Die VOC-Bestimmung wird dabei in einer Prüfkammer nach dem Tenax-Thermodesorptions-Verfahren mit nachgeschalteter GC/MS-Analyse durchgeführt.
- Die Einstufung in EMICODE-Klassen erfolgt entsprechend den nachstehenden Bezeichnungen und TVOC/TSVOC-Konzentrationsbereichen. Zur Produktkennzeichnung ist die zutreffende EMICODE-Klasse zu verwenden:

### 1) Verlegewerkstoffe, Klebstoffe und Bauprodukte

Parameter	EC 1 <sup>PLUS</sup>	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
TVOC nach 3 Tagen	≤ 750	≤ 1000	≤ 3000
TVOC nach 28 Tagen	≤ 60	≤ 100	≤ 300
TSVOC nach 28 Tagen	≤ 40	≤ 50	≤ 100
R-Wert basierend auf AgBB-NIK-Werten nach 28 Tagen	1	-	-
Summe der nicht bewertbaren VOC	≤ 40	-	-
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Summe von Form- und Acetaldehyd	≤ 0,05 ppm	≤ 0,05 ppm	≤ 0,05 ppm
Summe von flüchtigen K1A/K1B Stoffen nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1

### 2) Oberflächenbehandlungsmittel für Parkett, mineralische Böden und elastische Bodenbeläge

Parameter	EC 1 <sup>PLUS</sup>	EC 1	EC 2
	max. zulässige Konzentration [µg/m³]		
Summe TVOC + TSVOC nach 28 Tagen	≤ 100 davon max. 40 SVOC	≤ 150 davon max. 50 SVOC	≤ 450 davon max. 100 SVOC
Formaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Acetaldehyd nach 3 Tagen	≤ 50	≤ 50	≤ 50
Jeder flüchtige K1A/K1B Stoff nach 3 Tagen	≤ 10	≤ 10	≤ 10
Jeder flüchtige K1A/K1B Stoff nach 28 Tagen	≤ 1	≤ 1	≤ 1