



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

13373-10-1130

Staubschutztür

Product group: Covering fleece



Adolf Würth GmbH & Co. KG
Reinhold-Würth-Straße 12-17
74653 Künzelsau-Gaisbach



Product qualities:



Köttner

Helmut Köttner
Scientific Director
Freiburg, 09 December 2025



Product:

Staubschutztür

SHI Product Passport no.:

13373-10-1130



Contents

■ SHI Product Assessment 2024	1
Product labels	2
Legal notices	3
Technical data sheet/attachments	4

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

Staubschutztür

SHI Product Passport no.:

13373-10-1130



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Assessment
SHI Product Assessment		Beneficial



Product:

Staubschutztür

SHI Product Passport no.:

13373-10-1130



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



Product:

Staubschutztür

SHI Product Passport no.:

13373-10-1130



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Tel.: +49 761 59048170
info@sentinel-holding.eu
www.sentinel-holding.eu

Staubschutztür

Wiederverschließbarer Türdurchgang aus staubdichtem Spezialvlies mit Reißverschluss - Befestigung mit beiliegendem doppelseitigem Klebeband

Staubdichtes, aber luftdurchlässiges Spezialvlies

- Angrenzende Räume werden bei Renovierungsarbeiten vor Staub geschützt
- Zusätzlich Sichtschutz und Schutz vor ungewolltem Betreten des Raums
- Luftdurchlässigkeit ermöglicht Frischluftzufuhr

Hochwertiger, beidseitig leicht zu öffnender Reißverschluß

Flexibel einsetzbar für alle Türmaße bis maximal 1 m x 2,10 m verwendbar

Einfachste Montage - Staubschutztür wird mit dem doppelseitigem Klebeband befestigt und kann rückstandsfrei von den meisten Untergründen entfernt werden

Wiederverwendbar



Werkstoff	Polypropylen-Vlies
Klebstoffbasis	Acrylat-Dispersion
Höhe	2,1 m
Breite	1,1 m
Durchgangshöhe	1,9 m
Durchgangsbreite	0,7 m
Klebebandlänge	7 m
Klebebandbreite	38 mm
Verarbeitungstemperatur min.	15 °C
Einsatzdauer max.	7 d
Lagerfähigkeit ab Herstellung	24 Monate
Lagerfähigkeit ab Herstellung Bedingung	bei 20 °C und 50% Luftfeuchtigkeit

Art.-Nr. 0992 419 990

VE: 1 / 5

Details/Anwendung

Alle Tätigkeiten, bei denen angrenzende Räume vor Staub oder Schmutz geschützt werden sollen, z.B. bei Renovierungen, Elektro- oder Sanitärarbeiten, Malerarbeiten, im Trockenbau oder beim Parkettschleifen.



Hinweis

Klebeband darf im verklebten Zustand nicht direkter Sonneneinstrahlung ausgesetzt werden. Der Untergrund muss trocken, staub- und fettfrei sein. Lack oder Lasur muss vollständig durchgehärtet sein. Nicht anzuwenden auf Marmor- und Granituntergründen, stark saugenden Untergründen und Untergründen mit ungenügender innerer Stabilität wie bei schlecht haftendem Lack. Wir empfehlen eine Probeverklebung an unauffälliger Stelle durchzuführen.