



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

14792-10-1008

Gira System 3000 Raumtemperaturregler BT

Product group: Electrical installation - Other

GIRA

Gira Giersiepen GmbH & Co. KG
Dahlienstraße 12
42477 Radevormwald



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



GIRA

Contents

 SHI Product Assessment 2024	1
 QNG - Qualitätssiegel Nachhaltiges Gebäude	2
 DGNB New Construction 2023	3
 DGNB New Construction 2018	4
 BNB-BN Neubau V2015	5
 EU taxonomy	6
 BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC $\leq 300 \mu\text{g}/\text{m}^3$ Formaldehyd $\leq 24 \mu\text{g}/\text{m}^3$	Indoor Air Quality Certified
Valid untill: 22 February 2026			



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment
Verification: Einhaltung Blei und Cadmium $\leq 0,10$ % durch Konformitätserklärung vom 06. Februar 2023.			



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control			Not relevant for assessment



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment



Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:

Gira System 3000 Raumtemperaturregler BT

SHI Product Passport no.:

14792-10-1008

GIRA

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/kriterien%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

06.02.2023

Konformitätserklärung RoHS

Sehr geehrte Damen und Herren,

die Elektro- und Elektronikgeräte-Stoff-Verordnung (ElektroStoffV, zur Umsetzung der Richtlinie (EU) 2015/863 der Kommission vom 31. März 2015 [RoHS II]) verbietet das Inverkehrbringen von Elektro- und Elektronikgeräten im Sinne des § 2 Nr. 1 der ElektroStoffV, wenn darin homogene Werkstoffe verarbeitet sind, die einen oder mehrere der in der Verordnung genannten Stoffe in einer höheren als der zulässigen Höchstkonzentration enthalten.

Betroffen sind zum aktuellen Zeitpunkt Blei, Quecksilber, sechswertiges Chrom, polybromiertes Biphenyl (PBB), polybromierte Diphenylether (PBDE), Di(2-ethylhexyl)phthalat (DEHP), Butylbenzylphthalat (BBP), Dibutylphthalat (DBP) und Diisobutylphthalat (DIBP), die je homogenem Werkstoff die zulässige Höchstkonzentration von 0,1 Gewichtsprozent nicht überschreiten dürfen, sowie Cadmium, das nur bis zu einer Höchstkonzentration von 0,01 Gewichtsprozent je homogenem Werkstoff enthalten sein darf.

Die von Gira hergestellten Elektro- und Elektronikgeräte im Sinne der ElektroStoffV beinhalten keine der dort genannten Stoffe in einer höheren als der zugelassenen Höchstkonzentration, unter Berücksichtigung der Ausnahmen der Anhänge III und IV der RoHS-Richtlinie.

Mit freundlichen Grüßen



Christian Feltgen
Geschäftsführer

Abdeckrahmen Gira Standard 55 Reinweiß glänzend



Spezifikation	Bestell-Nr.	VE	EUR/Stück o. MWSt.	PS	EAN
 1fach	0211 03	10/100	3,09	21	4010337211037
 1,5fach	1001 03	10	4,17	01	4010337881308
 2fach	0212 03	10/100	5,28	21	4010337212034
 2fach ohne Mittelsteg	1002 03	10	3,90	01	4010337001607
 3fach	0213 03	10/100	9,31	01	4010337213031
 4fach	0214 03	1/5	16,10	01	4010337214038
 5fach	0215 03	1/5	26,48	01	4010337215035

Merkmale

- Bruchsicher.

Hinweise

- Auch für Kanalinstallationen geeignet.
 - Abdeckrahmen (1- bis 5fach) in Verbindung mit Dichtungsset auch für die Montage wassergeschützt Unterputz IP44 geeignet.
-

System 3000 Raumtemperaturregler-Einsatz mit Fühleranschluss



Spezifikation	Bestell-Nr.	VE	EUR/Stück o. MWSt.	PS	EAN
	5395 00	1/5	110,15	02	4010337036128

Merkmale

- Schalten von Elektrofußbodenheizungen und thermischen Stellantrieben.
- Ausgangssignal: Pulsweitenmodulation (PWM) oder Zweipunktregelung (Ein/Aus).
- Eingang zum Umschalten auf Kühlbetrieb.
- Unterbricht nach 60 Minuten den Heizvorgang (Überhitzungsschutz eines Heizgerätes).
- Anschluss eines Fernfühlers (Zubehör) möglich.

Kombination mit RF Bedieneinsatz 1fach / 2fach für KNX

- Heizungsaktor 1fach
- Sensorkanal 1fach bzw. 2fach.
- Lokale Steuerung des System 3000 Einsatzes möglich.
- Funksteuerung von anderen Geräten für KNX als Sensor möglich.
- Temperaturerfassung.
- Funktionsauswahl des Einsatzes für Raumtemperaturregler:
Ansteuerung von 230 V-Stellantrieben, Heiz-, Kühlbetrieb, Heiz- und Kühlbetrieb, Umschaltung des Heiz- oder Kühlbetriebs durch Kommunikationsobjekt oder Nebenstelleneingang. PWM- und 2-Punkt-Regler, absolute und relative Sollwertvorgabe, Wärmebedarfsteuerung inkl. Kaskadierung, Ventilschutzfunktion.
Zyklische Überwachung der Fußbodentemperatur, Servicebetrieb für Ventilausgang, Frostschutz-Funktion (automatisch oder per Kommunikationsobjekt), Abgleich des Temperatursensors, Boost-Funktion, Sommer- und Winterkompensation.
Nebenstelleneingang dient zur Umschaltung zwischen dem Heiz- und Kühlbetrieb.

Technische Daten

Nennspannung:	AC 230 V, 50/60 Hz
Stand-by:	0,1 bis 0,5 W
Schaltstrom:	10 mA bis 16 A
Anschlussleistung:	max. 3600 W
Empfohlene Montagehöhe:	1,50 m
Einbautiefe:	24 mm
Montage:	in Gerätedose nach DIN 49073

Umgebungstemperatur:

-5 °C bis +45 °C

System 3000 Raumtemperaturregler BT



Spezifikation	Bestell-Nr.	VE	EUR/Stück o. MWSt.	PS	EAN
 Cremeweiß glänzend	5394 01	1/5	136,15	02	4010337055273
 Reinweiß glänzend	5394 03	1/5	136,15	02	4010337055280
 Reinweiß seidenmatt	5394 27	1/5	136,15	02	4010337055464
 Farbe Alu	5394 26	1/5	142,22	02	4010337055457
 Anthrazit	5394 28	1/5	139,80	02	4010337055525
 Schwarz matt	5394 005	1/5	142,22	02	4010337055679
 Grau matt	5394 015	1/5	142,22	02	4010337087328
 Edelstahl	5394 600	1/5	149,02	02	4010337055655

Merkmale

- Bedienung und Programmierung mit mobilem Endgerät (Smartphone oder Tablet) über Bluetooth® mit der Gira System 3000 App.
- Bedienung über kapazitive Sensorfläche.
- Manuelles und zeitgesteuertes Regeln der Raumtemperatur.

Funktionen am Aufsatz

- Aktuelle Uhrzeit als Schaltzeitpunkt speicherbar, Schnellprogrammierung.
- Automatische Sommer-/Winterzeitumstellung, abschaltbar.
- Zeitschaltuhr mit drei Speicherbereichen je Speicherbereich Komfort- und Absenkezeitpunkt für Mo-Fr und Sa+So.
- Einstellung einer Komfort-, Absenk-, Kühl- und Frostschutztemperatur.
- Reglerausgang: Pulsweitenmodulation (PWM) oder 2-Punkt-Regelung.
- Aufheizoptimierung (Temperatur wird zur eingestellten Zeit erreicht).
- Anpassung an Ventile (stromlos offen oder stromlos geschlossen).
- Aktivieren des Kühlbetriebs über den Einsatz.
- Unterstützt internen und externen Temperaturfühler.
- Temperatursturzerkennung.
- Bediensperre.
- Ventilschutzfunktion.
- Display schaltet nach 2 Minuten aus, Dauerhafte Anzeige der aktuellen Uhrzeit möglich.

Funktionen mit Gira System 3000 App

- Wochenzeitschaltuhr mit 40 individuell programmierbaren Schaltpunkten und Temperaturen.
- Urlaubsmodus (Beginn, Ende, Temperatur).
- Boostfunktion: Schnellaufheizen für max. 5 Minuten.
- Sperre der vor Ort Bedienung möglich.
- Einbinden eines externen Temperatursensors über Bluetooth®.
- Minimale und maximale Temperaturwerte einstellbar.
- Kopieren von Einstellungen und Zeitprogrammen auf weitere Aufsätze möglich.
- Die Kombination des Aufsatzes 5393xx mit 540700 ist erst ab I05 (Index) möglich.

Technische Daten

Ganggenauigkeit pro Monat:	± 10 s
Gangreserve:	ca. 4 h
Funkfrequenz:	2,402 bis 2,480 GHz
Sendeleistung:	max. 2,5 mW, Klasse 2
Sendereichweite:	typ. 10 m
Umgebungstemperatur:	-5 °C bis +45 °C

Hinweise

- Bei Verbindung mit der Gira System 3000 App wird die Uhrzeit und das Datum aktualisiert.
-