



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

12174-10-1005

Bodomo Klassik

Product group: Floor coverings / Wall coverings - Laminate



Peter & Schaffart GmbH
Rosenkamp 10
42549 Velbert



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



Contents

 SHI Product Assessment 2024	1
 QNG - Qualitätssiegel Nachhaltiges Gebäude	2
 DGNB New Construction 2023	3
 DGNB New Construction 2018	4
 BNB-BN Neubau V2015	5
 EU taxonomy	6
 BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Wood-based floor coverings	TVOC $\leq 300 \mu\text{g}/\text{m}^3$ Formaldehyd $\leq 36 \mu\text{g}/\text{m}^3$	Indoor Air Quality Certified
Valid until: 24 October 2027			



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.3 Multi-layer wood parquet, bamboo coverings, and floor coverings on wood-based panels	VOC / Emissions / hazardous substances	QNG ready

Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	47c Wood-based materials in floor coverings	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	47c Floor coverings for indoor use (with wooden components)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.

Criteria	Quality level
ENV1.3 Responsible resource extraction	May positively contribute to the overall building score

Verification: PEFC Zertifikat vom 23.08.2022 des Produzenten. Übereinstimmung bestätigt.



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	47a Industrially manufactured products	Formaldehyde	Quality level 4

Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	zb Wood-based floor coverings – also systems	VOC / hazardous substances	Quality level 5
Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.			

Criteria	Assessment
1.1.7 Nachhaltige Materialgewinnung	May positively contribute to the overall building score
Verification: PEFC Zertifikat vom 23.08.2022 des Produzenten. Übereinstimmung bestätigt.	



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Floor coverings (including associated adhesives and sealants)	Substances according to Annex C, formaldehyde, carcinogenic VOCs category 1A/1B	EU taxonomy compliant
Verification: Blauer Engel Zertifizierung des Produzenten. Übereinstimmung bestätigt.			



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Flooring materials (including floor levelling compounds and resin flooring)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality

Verification: TÜV PROFICERT-product Interior PREMIUM vom 02.02.2024 des Produzenten. Übereinstimmung bestätigt.



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



Product:

Bodomo Klassik

SHI Product Passport no.:

12174-10-1005



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/Pr%C3%BCfverfahren%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

Technisches Datenblatt / Bodomo Klassik

Direktbeschichteter Laminatboden, Beanspruchungsklasse nach EN 13329: **23/31 - AC3**

7 mm 31/AC3

DIMENSIONEN

Format	Dicke	$7 \pm 0,50 \text{ mm} \cdot d_{\text{max}} - d_{\text{min}} \leq 0,50 \text{ mm}$		
	Länge	$1285 \pm 0,50 \text{ mm}$		
	Breite	$192 \pm 0,10 \text{ mm} \cdot b_{\text{max}} - b_{\text{min}} \leq 0,20 \text{ mm}$		
Profil	längs	twin clic	quer	twin clic
Fuge	längs	-	quer	-

TOLERANZEN

Rechtwinkligkeit	EN 13329	$\leq 0,20 \text{ mm}$
Kantengeradheit	EN 13329	$\leq 0,30 \text{ mm}$
Querwölbung	EN 13329	konkav: $\leq 0,15\%$ · konvex: $\leq 0,20\%$
Längswölbung	EN 13329	konkav: $\leq 0,50\%$ · konvex: $\leq 1,00\%$
Fugenöffnung	EN 13329	Mittelwert: $\leq 0,15 \text{ mm}$ · Maximum: $\leq 0,20 \text{ mm}$
Höhenversatz	EN 13329	Mittelwert: $\leq 0,10 \text{ mm}$ · Maximum: $\leq 0,15 \text{ mm}$
Riegelversatz		$\pm 2 \text{ mm}$

PRÜFUNGEN


Abriebbeanspruchung	EN 13329	AC3 (≥ 2000 Umdr.)
Stoßbeanspruchung	EN 13329	kleine Kugel $\geq 10 \text{ mm}$ · große Kugel $\geq 350 \text{ mm}$
Fleckunempfindlichkeit	Gruppe 1 & 2	Grad 5
	Gruppe 3	$\geq \text{Grad } 4$
Stuhlrollenversuch	EN 13329	keine sichtbaren Veränderungen oder Schäden wie in EN 425:2002 definiert
Auswirkung eines Möbelfußes	EN 13329	keine sichtbare Veränderung bei Prüfung mit Fuß Typ 0
Dickenquellung	EN 13329	$\leq 18\%$
Resteindruck	EN 13329	$\leq 0,05 \text{ mm}$
Lichtechtheit	EN 13329	Graumaßstabsstufe ≥ 4 bei Typverfärbung 6 des Blaumaßstabes
Maßänderungen nach Änderungen der relativen Luftfeuchte	EN 13329	längs $\leq 0,9 \text{ mm}$ · quer $\leq 0,9 \text{ mm}$
Abhebefestigkeit	EN 13329	$\geq 1,0 \text{ N/mm}^2$

UMWELTEIGENSCHAFTEN

Formaldehydemission	EN 16516	Klasse E1
---------------------	----------	-----------

PHYSIKALISCHE EIGENSCHAFTEN

Brandverhalten	EN 13501-1	Cfl s1
Gleitwiderstand	EN 13893	Technische Klasse DS
Wärmedurchlasswiderstand	EN 12667	$0,062 \text{ (m}^2\text{K)/W} \pm 15\%$
Wärmeleitfähigkeit	EN 12664	$0,110 \text{ W/(m}^*\text{K)} \pm 15\%$



* The guarantee is valid for domestic use according to the conditions of guarantee

Das Datenblatt wird regelmäßig dem Stand der Technik angepasst.
Diese Ausgabe ersetzt alle früheren Ausgaben und die ohne Datum.
Die Gültigkeit beginnt mit der Erstellung. Stand 09/2025

Peter & Schaffart GmbH
Rosenkamp 10
42549 Velbert
Tel. 0800 800 26336
info@bodomo.de
www.bodomo.de