



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

14860-10-1030

RAVATHERM XPS 250 PB

Product group: XPS



RAVAGO BUILDING SOLUTIONS GERMANY GMBH
Gernsheimer Str. 1
64673 Zwingenberg



Product qualities:



Köttner
Helmut Köttner
Scientific Director
Freiburg, 10 December 2025



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



Contents

■ SHI Product Assessment 2024	1
■ QNG - Qualitätssiegel Nachhaltiges Gebäude	2
■ DGNB New Construction 2023	3
■ DGNB New Construction 2018	5
■ BNB-BN Neubau V2015	6
■ EU taxonomy	7
■ BREEAM DE Neubau 2018	8
Product labels	9
Legal notices	10
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Insulation materials	TVOC ≤ 300 µg/m ³ Formaldehyd ≤ 24 µg/m ³	Indoor Air Quality Certified
Valid until: 16 July 2026			

Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	12.1 Rigid plastic foam insulation boards and spray foams	Halogenated propellants / SVHC: HBCD, TCEP / emissions	QNG ready

Verification: Technisches Datenblatt

Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	40 Synthetic foam insulation for buildings and building services	Halogenated propellants	Quality level 4

Verification: Technisches Datenblatt

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score

Verification: SHI-Schadstoffgeprüft

Criteria	Assessment
ENV1.1 Climate action and energy (*)	May positively contribute to the overall building score

Verification: Wärmedämmung, EPD, ETA -> Lebensdauer größer 50 Jahre

Criteria	Assessment
ECO1.1 Life cycle cost (*)	May positively contribute to the overall building score

Verification: Wärmedämmung



Criteria	Assessment
ECO2.6 Climate resilience (*)	May positively contribute to the overall building score
Verification: Wärmedämmung	

Criteria	Assessment
SOC1.1 Thermal comfort (*)	May positively contribute to the overall building score
Verification: Wärmedämmung	

Criteria	Assessment
TEC1.3 Quality of the building envelope (*)	May positively contribute to the overall building score
Verification: Wärmedämmung	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	40 Synthetic foam insulation for buildings	Halogenated propellants / SVHC: HBCD, TCEP / emissions	Quality level 4

Verification: Technisches Datenblatt



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	40 Synthetic insulating materials for buildings and building services	Halogenated propellants	Quality level 4

Verification: Technisches Datenblatt



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	36a Mineral and non-mineral external wall insulations (external wall paints see Position 6, plasters see Position 35)	Biocides / hazardous substances / halogenated blowing agents	Quality level 3

Verification: Zusätzlich gilt Pos. 32a: Technisches Datenblatt

Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant
Verification: SHI-Schadstoffgeprüft			



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Ceiling, wall, and acoustic and thermal insulation materials	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality

Verification: Prüfbericht des Instituts Eurofins vom 23.04.2020 / Prüfbericht Nr. 392-2020-00060601_A_DE. Konformitätserklärung vom 22.01.2024 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt.



Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



The IBU ("Institut Bauen und Umwelt e.V.") is an initiative of building product manufacturers committed to sustainability in construction. It serves as the programme operator for Environmental Product Declarations (EPDs) in accordance with the EN 15804 standard. The IBU EPD programme provides comprehensive life cycle assessments and environmental impact data for construction products, supported by independent third-party verification.

Product:

RAVATHERM XPS 250 PB

SHI Product Passport no.:

14860-10-1030



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Tel.: +49 761 59048170
info@sentinel-holding.eu
www.sentinel-holding.eu



SICHERHEITSDATENBLATT

RAVAGO BUILDING SOLUTIONS

Sicherheitsdatenblatt gemäß Reg. (EU) No 2015/830

Produktnname: RAVATHERM™ XPS 250-PB-B1

Extruded Polystyrene Foam

Überarbeitet am: 01.12.2019

Version: 1.3

Druckdatum: 19.12.2019

RAVAGO BUILDING SOLUTIONS Ermutigt Sie und erwartet von Ihnen aufgrund wichtiger Informationen im gesamten Dokument, das SDS vollständig zu lesen und zu verstehen. Wir erwarten von Ihnen, die in diesem Dokument aufgezeigten Vorsichtsmaßnahmen zu befolgen, es sei denn, Ihre Nutzungsbedingungen erfordern andere angemessene Methoden oder Maßnahmen.

ABSCHNITT 1: BEZEICHNUNG DES STOFFS BEZIEHUNGSWEISE DES GEMISCHS UND DES UNTERNEHMENS

1.1 Produktidentifikator

Produktnname: RAVATHERM™ XPS 250-PB-B1 Extruded Polystyrene Foam

1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird

Identifizierte Verwendungen: Wärmeisolierung.

1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

BEZEICHNUNG DES UNTERNEHMENS

RAVAGO BUILDING SOLUTIONS GERMANY GMBH
VALUE PARK Y51
06258 SCHKOPAU
GERMANY

Kundeninformationen:

info@ravatherm.com

ABSCHNITT 2: MÖGLICHE GEFAHREN

2.1 Einstufung des Stoffs oder Gemischs

Einstufung gemäß der Verordnung (EG) Nr. 1272/2008:

Kein gefährlicher Stoff oder gefährliches Gemisch gemäß der Verordnung (EG) Nr. 1272/2008.

2.2 Kennzeichnungselemente

Etikettierung gemäß Verordnung (EC) No 1272/2008 [CLP/GHS]:

Kein gefährlicher Stoff oder gefährliches Gemisch gemäß der Verordnung (EG) Nr. 1272/2008.

2.3 Sonstige Gefahren

Keine Daten verfügbar

TM Marke von Ravago S.A.

TM Marke von DDP Specialty Electronic Materials US, Inc. ("DDP") oder verbundenen Unternehmen

2.3 Sonstige Gefahren

Keine Daten verfügbar

ABSCHNITT 3: ZUSAMMENSETZUNG/ANGABEN ZU BESTANDTEILEN**3.2 Gemische**

Das Produkt ist ein Erzeugnis.

CAS RN / EG-Nr. / INDEX-Nr.	REACH Registrierungsnu mmer	Konzentration	Bestandteil	Einstufung: VERORDNUNG (EG) Nr. 1272/2008
CAS RN - EG-Nr. - INDEX-Nr. -	-	100,0%	Polystyrol Schaumstoffe	Nicht klassifiziert

Wenn in diesem Produkt enthalten, werden jegliche oben aufgeführten nicht klassifizierten Komponenten, für welche in Abschnitt 8 keine länderspezifischen Arbeitsplatzgrenzwerte angegeben sind, auf freiwilliger Basis offengelegt.

ABSCHNITT 4: ERSTE-HILFE-MAßNAHMEN**4.1 Beschreibung der Erste-Hilfe-Maßnahmen**

Allgemeine Hinweise: Bei möglicher Exposition, siehe Abschnitt 8 hinsichtlich spezieller persönlicher Schutzausrüstung.

Einatmen: Person an die frische Luft bringen; bei Beschwerden Arzt aufsuchen.

Hautkontakt: Mit viel Wasser abwaschen.

Augenkontakt: Augen sorgfältig für einige Minuten mit Wasser ausspülen. Entfernen der Kontaktlinsen innerhalb der ersten 1-2 Minuten und Augenspülung für einige weitere Minuten fortsetzen. Bei auftretenden Beeinträchtigungen, Arzt aufsuchen vorzugsweise einen Augenarzt. Kann Verletzung durch mechanische Einwirkung verursachen.

Verschlucken: Keine medizinische Notfallbehandlung erforderlich.

4.2 Wichtigste akute und verzögert auftretende Symptome und Wirkungen: Neben den Informationen, die in der Beschreibung unter "Erste-Hilfe-Maßnahmen" (oberhalb) und "Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung" (unterhalb) aufgeführt sind, sind weitere zusätzliche Symptome und Wirkungen in Abschnitt 11 "Toxikologische Angaben" beschrieben.

4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

Hinweise für den Arzt: Kein spezifisches Antidot bekannt. Die Behandlung einer Exposition sollte sich auf die Kontrolle der Symptome und des klinischen Zustandes des Patienten richten.

ABSCHNITT 5: MAßNAHMEN ZUR BRANDBEKÄMPFUNG

5.1 Löschmittel

Geeignete Löschmittel: Wassernebel oder Wassersprühnebel. Trockenlöschmittel. Kohlendioxid-Feuerlöscher. Schaum.

Ungeeignete Löschmittel: Keine Daten verfügbar

5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren

Gefährliche Verbrennungsprodukte: Im Brandfall kann der Rauch neben dem Ausgangsmaterial Verbrennungsprodukte mit nicht bestimmbaren toxisch und/oder reizend wirkenden Zusammensetzungen enthalten. Bei Schweißbrand oder Brand entwickeln sich Kohlenmonoxid, Kohlendioxid und Kohlenstoff. Verbrennungsprodukte können u.a. enthalten: Halogenwasserstoffe. Beruhend auf Toxizitätstests der Verbrennung ergibt sich, daß die Wirkungen der Verbrennung dieses Schaumstoffs nicht toxischer ist als die Wirkung der Verbrennung von gängigen Baumaterialien wie Holz.

Besondere Gefährdungen bei Feuer und Explosion: Mechanisches Schneiden, Zerkleinern oder Sägen kann zur Bildung von Stäuben führen. Zur Vermeidung einer Staubexplosion sollte eine Staubansammlung vermieden werden. Bei Verbrennung des Produkts entsteht dichter Rauch.

5.3 Hinweise für die Brandbekämpfung

Brandbekämpfungsmaßnahmen: Gefahrenbereich absperren und unbeteiligte Personen fernhalten. Mit Wasser kühlen und gründlich tränken, um eine Wiederentzündung zu verhindern. Falls das Material geschmolzen ist, nicht mit direktem Wasserstrahl löschen. Wassersprühnebel oder Schaum verwenden. Den umgebenden Bereich mit Wasser kühlen, um die Brandzone eingegrenzt zu halten.

Besondere Schutzausrüstung für die Brandbekämpfung: Zugelassenen ortsunabhängigen Überdruck-Preßluftatmer bzw. umluftunabhängiges Atemschutzgerät anlegen sowie Feuerwehrschutzkleidung (Feuerwehr-Helm mit Nackenschutz, -Schutanzug, -Schutzschuhwerk und -Schutzhandschuhe) tragen. Sollte keine Schutzkleidung vorhanden sein, Feuer aus sicherer Entfernung oder von geschützter Stelle aus bekämpfen.

ABSCHNITT 6: MAßNAHMEN BEI UNBEABSICHTIGTER FREISETZUNG

6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren: Es sind keine speziellen Maßnahmen erforderlich.

6.2 Umweltschutzmaßnahmen: Es sind keine speziellen Maßnahmen erforderlich.

6.3 Methoden und Material für Rückhaltung und Reinigung: Verschüttetes Produkt wenn möglich aufnehmen. Siehe Abschnitt 13, Hinweise zur Entsorgung, für weitere Informationen.

6.4 Verweis auf andere Abschnitte: Falls erforderlich, wurden Verweise zu anderen Abschnitten in den vorherigen Teilabschnitten angegeben.

ABSCHNITT 7: HANDHABUNG UND LAGERUNG

7.1 Schutzmaßnahmen zur sicheren Handhabung: Beim Schneiden des Produktes kann in den Zellen verbliebenes Treibmittel freigesetzt werden. Hier ist für ausreichende Belüftung zu sorgen und zu sichern, daß lokale Konzentrationen unterhalb des unteren Zündbereiches gehalten werden. Mechanisches Schneiden, Zerkleinern oder Sägen kann zur Bildung von Stäuben führen. Zur Vermeidung einer Staubexplosion sollte eine Staubansammlung vermieden werden. Produkt ist brennbar und kann bei nicht sachgemäßer Anwendung eine Brandgefahr darstellen. Nach dem Einbau sollte dieses Produkt genügend geschützt werden, wie es in den nationalen Bauvorschriften oder der Anweisung zum Einbau beschrieben ist.

7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten: Während des Versands, der Lagerung, Anbringung und Anwendung sollte dieses Material keinen Flammen oder anderen Zündquellen ausgesetzt werden.

7.3 Spezifische Endanwendungen: Weitere Information für dieses Produkt findet sich im technischen Datenblatt.

ABSCHNITT 8: BEGRENZUNG UND ÜBERWACHUNG DER EXPOSITION/PERSÖNLICHE SCHUTZAUSRÜSTUNGEN

8.1 Zu überwachende Parameter

So Grenzwerte für Arbeitsstoffe festgelegt wurden, sind diese nachfolgend aufgeführt.

Obwohl einige Bestandteile des Produktes Luftgrenzwerte haben, würde man unter Bedingungen der normalen Handhabung aufgrund des physikalischen Zustandes des Produktes keine Exposition erwarten.

8.2 Begrenzung und Überwachung der Exposition

Technische Kontrollmaßnahmen: Es ist für lokale Entlüftung oder für andere technische Voraussetzungen zu sorgen, um die Arbeitsplatzgrenzwerte einzuhalten. Wenn keine Arbeitsplatzgrenzwerte vorliegen, sollte eine generelle Be- und Entlüftung für die meisten Arbeitsgänge ausreichend sein. Bei manchen Arbeitsgängen kann örtliche Absaugung notwendig sein.

Individuelle Schutzmaßnahmen

Augen-/Gesichtsschutz: Augenschutz sollte nicht nötig sein. Beim der Herstellung des Produktes sind Sicherheitsbrillen (mit Seitenschutz) empfohlen. Sicherheitsbrillen (mit Seitenschutz) sollten den Anforderungen der EN 166 oder ähnlichen entsprechen. Bei möglicher Exposition gegenüber Partikeln, die Augenbeschwerden hervorrufen könnten, Schutzbrille tragen. Schutzbrillen sollten DIN EN 166 oder ähnlicher Norm entsprechen.

Hautschutz

Handschutz: Handschuhe zum Schutz gegen mechanische Verletzungen tragen. Die Auswahl der Handschuhe hängt von der Art der Arbeit ab.

Anderer Schutz: Außer sauberer, körperbedeckender Kleidung ist keine weitere Maßnahme erforderlich.

Atemschutz: Bei möglicher Überschreitung der Arbeitsplatzgrenzwerte sollte Atemschutz getragen werden. Wenn es keine Arbeitsplatzgrenzwerte gibt, sollte beim Auftreten schädigender Wirkungen wie Atemwegsreizung oder körperlicher Beschwerden oder wenn es durch den Risikobewertungsprozess angezeigt ist Atemschutz getragen werden. Wenn bei bestimmten Verfahrensweisen (einschließlich aber nicht begrenzt auf Sägen, Fräsen und Schneiden mit heißem Drath) Atemschutz erforderlich ist soll ein zugelassenes Filtergerät verwendet werden.

Bei Staub- oder Nebelbildung zugelassene Vollmaske mit Partikelfilter benutzen.
Folgende CE-zugelassene Atemschutzmaske ist zu verwenden:
Kombinationsfilter für organische Gase und Dämpfe mit Partikelfilter, Typ AP2.

Begrenzung und Überwachung der Umweltexposition

Siehe ABSCHNITT 7: Handhabung und Lagerung und ABSCHNITT 13:
Entsorgungshinweise für Maßnahmen zur Verhinderung übermäßiger Umweltexposition
während der Verwendung und während der Abfallentsorgung.

ABSCHNITT 9: PHYSIKALISCHE UND CHEMISCHE EIGENSCHAFTEN

9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften Aussehen

Form	Schaum
Farbe	blau oder grau
Geruch	Geruchlos
Geruchsschwellenwert	Geruchlos
pH-Wert	Keine Daten verfügbar
Schmelzpunkt/Schmelzbereich	> 75 °C <i>Literaturdaten</i>
Gefrierpunkt	Keine Daten verfügbar
Siedepunkt (760 mmHg)	Keine Daten verfügbar
Flammpunkt geschlossener Tiegel	346 °C <i>Literaturdaten</i>
Verdampfungsgeschwindigkeit (Butylacetat = 1)	Keine Daten verfügbar
Untere Explosionsgrenze	Keine Daten verfügbar
Obere Explosionsgrenze	Keine Daten verfügbar
Dampfdruck	Keine Daten verfügbar
Relative Dampfdichte (Luft = 1)	Keine Daten verfügbar
Relative Dichte (Wasser = 1)	Keine Daten verfügbar
Wasserlöslichkeit	unlöslich
Verteilungskoeffizient: n-Octanol/Wasser	Keine Daten verfügbar
Selbstentzündungstemperatur	491 °C <i>Literaturdaten</i>
Zersetzungstemperatur	> 300 °C <i>Literaturdaten</i>
Kinematische Viskosität	Keine Daten verfügbar
Explosive Eigenschaften	Keine Daten verfügbar
Oxidierende Eigenschaften	Keine Daten verfügbar

9.2 Sonstige Angaben

Feststoffdichte	20 - 70 kg/m ³ <i>Literaturdaten</i>
------------------------	---

Die physikalischen Daten in Abschnitt 9 entsprechen typischen Werten für dieses Produkt und sind nicht als Produktspezifikationen zu sehen.

ABSCHNITT 10: STABILITÄT UND REAKTIVITÄT

10.1 Reaktivität: Keine gefährlichen Reaktionen bekannt bei bestimmungsgemäßem Umgang.

10.2 Chemische Stabilität: Thermisch stabil im Temperaturbereich der Anwendung.

10.3 Möglichkeit gefährlicher Reaktionen: Polymerisation findet nicht statt.

10.4 Zu vermeidende Bedingungen: Zu vermeiden sind Temperaturen oberhalb 300°C.
Bei erhöhten Temperaturen kann sich das Produkt zersetzen. Direkte Sonneneinstrahlung vermeiden.

10.5 Unverträgliche Materialien: Kontakt vermeiden mit: Oxidationsmittel. Aldehyde. Amine.
Ester. Flüssige Brennstoffe. Organische Lösemittel.

10.6 Gefährliche Zersetzungprodukte: Zersetzt sich in der Regel nicht. Zersetzungprodukte hängen von der Temperatur, der Luftzufuhr und dem Vorhandensein anderer Stoffe ab.
Abbauprodukte können enthalten und sind nicht beschränkt auf: Aromatische Verbindungen.
Aldehyde. Halogenwasserstoffe. Polymerfragmente. Styrol. Ethylbenzol.

ABSCHNITT 11: TOXIKOLOGISCHE ANGABEN

Toxikologische Informationen werden in diesem Abschnitt aufgelistet, falls Daten zur Verfügung stehen.

11.1 Angaben zu toxikologischen Wirkungen

Akute Toxizität

Akute orale Toxizität

Bedingt durch den physikalischen Zustand ist ein Verschlucken unwahrscheinlich. Sehr geringe orale Toxizität. Gesundheitsschädliche Wirkungen werden bei Verschlucken kleiner Mengen nicht erwartet.

Akute dermale Toxizität

Aufnahme über die Haut ist aufgrund der physikalischen Eigenschaften unwahrscheinlich.

Akute inhalative Toxizität

Staub kann den oberen Atemtrakt (Nase und Rachen) reizen. Rauche/Dämpfe, die bei thermischen Prozessen wie beim Schneiden mit heißem Draht freigesetzt werden, können Atemwegsirritation verursachen.

Ätz-/Reizwirkung auf die Haut

Verletzung nur durch mechanische Einwirkung.
In der Regel nicht hautreizend.

Schwere Augenschädigung/-reizung

Feststoff oder Staub kann durch mechanische Einwirkung Reizung verursachen.
Rauch/Dämpfe, die bei thermischen Prozessen wie beim Schneiden mit heißem Draht freigesetzt werden, können Augenreizung verursachen.

Sensibilisierung

Für die Sensibilisierung der Haut:
Keine relevanten Angaben vorhanden.

Gegen die Sensibilisierung der Atemwege:
Keine relevanten Angaben vorhanden.

Systemische Zielorgantoxizität (einmalige Exposition)

Keine relevanten Angaben vorhanden.

Systemische Zielorgantoxizität (wiederholte Exposition)

Keine relevanten Angaben vorhanden.

Karzinogenität

Keine relevanten Angaben vorhanden.

Teratogenität

Keine relevanten Angaben vorhanden.

Reproduktionstoxizität

Keine relevanten Angaben vorhanden.

Mutagenität

Keine relevanten Angaben vorhanden.

Aspirationsgefahr

Stellt auf Grund der physikalischen Eigenschaften wahrscheinlich keine Aspirationsgefahr dar.

ABSCHNITT 12: UMWELTBEZOGENE ANGABEN

Ökotoxikologische Informationen werden in diesem Abschnitt aufgelistet, wenn diese Daten zur Verfügung stehen.

12.1 Toxizität

Akute Fischtoxizität

Es wird keine akute Giftigkeit gegenüber aquatischen Organismen erwartet.

12.2 Persistenz und Abbaubarkeit

Biologische Abbaubarkeit: Unter Sonneneinstrahlung ist ein photochemischer Abbau der Oberfläche zu erwarten. Eine nennenswerte Biodegradation ist nicht zu erwarten.

12.3 Bioakkumulationspotenzial

Bioakkumulation: Aufgrund des relativ hohen Molekulargewichtes ($MG > 1000$) ist keine Biokonzentration zu erwarten.

12.4 Mobilität im Boden

Im Erdreich: Vom Material wird erwartet, daß es im Erdboden verbleibt.

12.5 Ergebnisse der PBT- und vPvB-Beurteilung

Dieser Stoff wurde hinsichtlich Persistenz, Bioakkumulierbarkeit und Toxizität (PBT) nicht bewertet.

12.6 Andere schädliche Wirkungen

Produkt enthält keine ozonschädigenden Komponenten.

ABSCHNITT 13: HINWEISE ZUR ENTSORGUNG

13.1 Verfahren der Abfallbehandlung

Es sollten alle Möglichkeiten ausgeschöpft werden, das Material wiederzuverwerten. Dieses Produkt kann vorzugsweise durch Verbrennung in zugelassenen Anlagen oder in einigen Ländern in zugelassenen Deponien entsorgt werden. Unter Beachtung abfallrechtlicher Gesetze und Verordnungen entsorgen. Es wird empfohlen, daß Rauchgase von Verbrennungsanlagen, in denen das Produkt verbrannt wird, vor Abgabe in die Atmosphäre durch eine Gaswäsche geleitet werden.

Die definitive Zuordnung dieses Materials zur entsprechenden Europäischen Abfallgruppe und daher zum passenden Europäischen Abfallschlüssel hängt von der Endanwendung dieses Materials ab. Setzen Sie sich mit dem autorisierten Abfallentsorger in Verbindung.

ABSCHNITT 14: ANGABEN ZUM TRANSPORT

Einstufung für den Landtransport (ADR / RID):

14.1 UN-Nummer	Nicht anwendbar
14.2 Ordnungsgemäße UN-Versandbezeichnung	Kein Gefahrgut im Sinne der Transportvorschriften
14.3 Transportgefahrenklassen	Nicht anwendbar
14.4 Verpackungsgruppe	Nicht anwendbar
14.5 Umweltgefahren	Aufgrund zur Verfügung stehender Daten als nichtgefährlich eingestuft.
14.6 Besondere Vorsichtsmaßnahmen für den Verwender	Keine Daten vorhanden.

Einstufung für den Seeschiffstransport (IMO - IMDG-code):

14.1 UN-Nummer	Nicht anwendbar
14.2 Ordnungsgemäße UN-Versandbezeichnung	Not regulated for transport

14.3 Transportgefahrenklassen	Nicht anwendbar
14.4 Verpackungsgruppe	Nicht anwendbar
14.5 Umweltgefahren	Aufgrund zur Verfügung stehender Daten als nichtmeeresverschmutzend eingestuft.
14.6 Besondere Vorsichtsmaßnahmen für den Verwender	Keine Daten vorhanden.
14.7 Massengutbeförderung gemäß Anhang I oder II des MARPOL-Übereinkommens 73/78 und gemäß IBC oder IGC-Code.	Consult IMO regulations before transporting ocean bulk

Einstufung für den Lufttransport (IATA-DGR):

14.1 UN-Nummer	Nicht anwendbar
14.2 Ordnungsgemäße UN-Versandbezeichnung	Not regulated for transport
14.3 Transportgefahrenklassen	Nicht anwendbar
14.4 Verpackungsgruppe	Nicht anwendbar
14.5 Umweltgefahren	Nicht anwendbar
14.6 Besondere Vorsichtsmaßnahmen für den Verwender	Keine Daten vorhanden.

Diese Information dient nicht dazu, alle spezifischen Regulatorien bzw. betrieblichen Anforderungen/Informationen bezüglich dieses Produktes zu vermitteln. Transportklassifizierungen können für verschiedene Behältergrößen und aufgrund regionaler oder länderspezifischer Regulatorien variieren. Zusätzliche Informationen bzgl. des Transportsystems können bei autorisierten Verkaufs- oder Kundendienstmitarbeitern erfragt werden. Es liegt in der Verantwortung des Transportunternehmens, alle entsprechenden Gesetze, Verordnungen und Regeln hinsichtlich des Transports dieses Produktes zu befolgen.

ABSCHNITT 15: RECHTSVORSCHRIFTEN

15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch

VO (EG) Nr. 1907/2006: REACH-Verordnung

Dieser Artikel enthält weder gefährliche Stoffe noch gefährliche Gemische, die unter normalen oder vernünftigerweise vorhersehbaren Gebrauchsbedingungen vorsätzlich freigesetzt werden. Die oben erwähnten Angaben über den REACH Registrierungsstatus wurden nach bestem Wissen und Gewissen bereitgestellt und zum oben erwähnten Zeitpunkt der Veröffentlichung als richtig erachtet. Es kann jedoch keine Garantie, ausdrücklich oder stillschweigend, gegeben werden. Es liegt in der Verantwortlichkeit des Käufers bzw. Verwenders sicherzustellen, dass sein/ihr Wissen über den Verordnungsstatus korrekt ist.

Wassergefährdungsklasse (Deutschland)
Nicht anwendbar für Erzeugnis.

15.2 Stoffsicherheitsbeurteilung
Nicht anwendbar

ABSCHNITT 16: SONSTIGE ANGABEN

Einstufung von Gemischen und verwendete Bewertungsmethode gemäß Verordnung (EG) Nr. 1272/2008 [CLP]

Dieses Produkt ist nach den EG-Kriterien nicht als gefährlich eingestuft.

Revision

Identifikationsnummer: 001 / De / Gültig ab: 01.12.2019 / Version: 1.3

Volltext anderer Abkürzungen

ADN - Europäisches Übereinkommens über die internationale Beförderung gefährlicher Güter auf Binnenwasserstrassen; ADR - Europäisches Übereinkommens über die internationale Beförderung gefährlicher Güter auf der Straße; AICS - Australisches Verzeichnis chemischer Substanzen; ASTM - Amerikanische Gesellschaft für Werkstoffprüfung; bw - Körpermengen; CLP - Verordnung über die Einstufung, Kennzeichnung und Verpackung von Stoffen, Verordnung (EG) Nr 1272/2008; CMR - Karzinogener, mutagener oder reproduktiver Giftstoff; DIN - Norm des Deutschen Instituts für Normung; DSL - Liste heimischer Substanzen (Kanada); ECHA - Europäische Chemikalienbehörde; EC-Number - Nummer der Europäischen Gemeinschaft; ECx - Konzentration verbunden mit x % Reaktion; ELx - Beladungsrate verbunden mit x % Reaktion; EmS - Notfallplan; ENCS - Vorhandene und neue chemische Substanzen (Japan); ErCx - Konzentration verbunden mit x % Wachstumsgeschwindigkeit; GHS - Global harmonisiertes System; GLP - Gute Laborpraxis; IARC - Internationale Krebsforschungsagentur; IATA - Internationale Luftverkehrs-Vereinigung; IBC - Internationaler Code für den Bau und die Ausrüstung von Schiffen zur Beförderung gefährlicher Chemikalien als Massengut; IC50 - Halbmaximale Hemmstoffkonzentration; ICAO - Internationale Zivilluftfahrt-Organisation; IECSC - Verzeichnis der in China vorhandenen chemischen Substanzen; IMDG - Code – Internationaler Code für die Beförderung gefährlicher Güter mit Seeschiffen; IMO - Internationale Seeschifffahrtsorganisation; ISHL - Gesetz- über Sicherheit und Gesundheitsschutz am Arbeitsplatz (Japan); ISO - Internationale Organisation für Normung; KECI - Verzeichnis der in Korea vorhandenen Chemikalien; LC50 - Lethale Konzentration für 50 % einer Versuchspopulation; LD50 - Lethale Dosis für 50 % einer Versuchspopulation (mittlere lethale Dosis); MARPOL - Internationales Übereinkommen zur Verhütung der Meeresverschmutzung durch Schiffe; n.o.s. - nicht anderweitig genannt; NO(A)EC - Konzentration, bei der keine (schädliche) Wirkung erkennbar ist; NO(A)EL - Dosis, bei der keine (schädliche) Wirkung erkennbar ist; NOELR - Keine erkennbare Effektladung; NZIoC - Neuseeländisches Chemikalienverzeichnis; OECD - Organisation für wirtschaftliche Zusammenarbeit und Entwicklung; OPPTS - Büro für chemische Sicherheit und Verschmutzungsverhütung (OSCPP); PBT - Persistente, bioakkumulierbare und toxische Substanzen; PICCS - Verzeichnis der auf den Philippinen vorhandenen Chemikalien und chemischen Substanzen; (Q)SAR - (Quantitative) Struktur-Wirkungsbeziehung; REACH - Verordnung (EG) Nr. 1907/2006 des Europäischen Parlaments und des Rates bezüglich der Registrierung, Bewertung, Genehmigung und Restriktion von Chemikalien; RID - Regelung zur internationalen Beförderung gefährlicher Güter im Schienenverkehr; SADT - Selbstbeschleunigende Zersetzungstemperatur; SDS - Sicherheitsdatenblatt; SVHC - besonders besorgniserregender Stoff; TCSI - Verzeichnis der in Taiwan vorhandenen chemischen Substanzen; TRGS - Technischen Regeln für Gefahrstoffe; TSCA – Gesetz zur Kontrolle giftiger Stoffe (Vereinigte Staaten); UN - Vereinte Nationen; vPvB - Sehr persistent und sehr bioakkumulierbar

RAVAGO BUILDING SOLUTIONS fordert jeden Kunden oder Empfänger dazu auf, dieses Sicherheitsdatenblatt sorgfältig zu lesen und wenn nötig sich die entsprechende Sachkenntnis zugänglich zu machen, um die in diesem Sicherheitsdatenblatt enthaltenen Daten und jegliche mit dem Produkt verbundenen Gefahren zu erkennen und zu verstehen. Die hierin gegebenen Informationen sind zum Zeitpunkt der Veröffentlichung nach unserem besten Wissen richtig. Jedoch wird dafür keine Garantie, ausdrücklich oder nicht ausdrücklich, gegeben. Die zu befolgenden Vorschriften unterliegen Änderungen und können an den verschiedenen Standorten voneinander abweichen. Es liegt daher in der Verantwortlichkeit des Käufers/Verwenders bei seinen Tätigkeiten die Gesetze auf Bundes-, Landes- und lokaler Ebene zu befolgen. Die hier gemachten Angaben betreffen nur das Produkt wie es versendet wird. Da die Verwendung des Produktes nicht der Kontrolle des Herstellers unterliegt, ist es die Pflicht des Käufers/Verwenders die nötigen Bedingungen für den sicheren Umgang mit dem Produkt festzulegen. Wegen der Zunahme von Informationsquellen für herstellerspezifische Sicherheitsdatenblätter fühlen wir uns nicht für Sicherheitsdatenblätter verantwortlich, die Sie nicht von uns erhalten haben. Sollten Sie Sicherheitsdatenblätter von einer anderen Quelle erhalten haben oder besteht Unsicherheit über die Aktualität der Sicherheitsdatenblätter bitten wir um Kontaktaufnahme, um die aktuellsten Sicherheitsdatenblätter zu erhalten.

DE

RAVATHERM™ XPS 250 PB

Dämmplatten aus Polystyrol-Extruderschaum mit rauer Oberfläche, zum Verputzen geeignet



- Platten mit glatten Kanten
- raue Oberfläche für gute Haftung für Kleber und Putz
- für innen- und außenliegende Dämmung (Wärmebrücken, Sockel)



RAVATHERM™ XPS, und RAVATHERM™ XPS X sind frei von HBCD. RAVATHERM™ XPS, und RAVATHERM™ XPS X werden mit CO₂ als Treibmittel hergestellt und sind somit auch frei von halogenierten Treibmitteln wie FCKW, HFCKW und HFKW.

RAVATHERM™ XPS 250 PB

Eigenschaften	CE-Code	Norm	Einheit	Wert
Zellinhalt				Luft
Dichte		DIN EN 1602	kg/m ³	33
Wärmeleitfähigkeit			λD	λBem gemäß DIN 4108-4
Dicke in mm	20	DIN EN 13164	W/(m·K)	0,033
Druckspannung oder Druckfestigkeit bei 10% Stauchung	CS(10\Y)	DIN EN 826	kPa	250
Zugfestigkeit	TR	DIN EN 1607	kPa	200
Linearer Wärmeausdehnungskoeffizient			mm/(m·K)	0,07
Dimensionsstabilität bei definierten Temperatur- (70°C) und Feuchtebedingungen 90%	DS(70/90)	DIN EN 1604	%	<5
Brandverhalten		DIN EN 13501-1	Euroclass	E
Abmessungen	Dicke	DIN EN 823	mm	20 (Klasse T2)
	Breite	Toleranzen	DIN EN 822	600
	Länge		DIN EN 822	1250
Kantenausbildung				glatte Kante
Oberflächenbeschaffenheit				gefräst
Anwendungsgebiete		DIN 4108-10		WAB, WAP, WI

CE-Code: XPS – EN 13164 – T2 – CS(10\Y)200 – DS(70,90) – TR200

Hinweis: Die Empfehlungen in Bezug auf Anwendungsmethoden und Gebrauch der Produkte beruhen auf der von RAVAGO erworbenen Erfahrung und Kenntnis der Eigenschaften von RAVATHERM Dämmplatten und werden nach bestem Wissen und Gewissen gemacht. Es wird hierdurch jedoch keine Haftung, Gewährleistung oder Garantie für Systeme oder Anwendungen übernommen. Eine Freistellung von Patentansprüchen kann hieraus nicht hergeleitet werden. Dieses Dokument stellt keine Verkaufsspezifikation dar. Die Angaben in diesem Prospekt stellen keine Zusicherung von Eigenschaften im Rechtssinne dar und werden nicht zum Inhalt eines Kaufvertrages. Pflichten und Haftung in Bezug auf den Verkauf von RAVATHERM Produkten bestimmen sich ausschließlich nach dem jeweils zugrunde liegenden Kaufvertrag. <https://www.ravagobuildingsolutions.com/de>

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	RBS Germany GmbH
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-RAV-20230375-CBD1-EN
Issue date	31/10/2023
Valid to	30/10/2028

RAVATHERM™ XPS (X) extruded polystyrene foam insulation with non-halogenated blowing agents

Ravago Building Solutions

www.ibu-epd.com | <https://epd-online.com>



General Information

Ravago Building Solutions

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-RAV-20230375-CBD1-EN

RAVATHERM™ XPS (X) extruded polystyrene foam insulation with non-halogenated blowing agents

Owner of the declaration

RBS Germany GmbH
Value Park Y51
06258 Schkopau
Germany

Declared product / declared unit

The EPD applies to 1 m³ of XPS board, with an average density of 34.4 kg/m³.

RAVATHERM™ XPS (X) extruded polystyrene foam boards produced by Ravago Building Solutions with a non-halogenated blowing agent system.

This declaration is based on the product category rules:

Insulating materials made of foam plastics, 01/08/2021
(PCR checked and approved by the SVR)

Issue date

31/10/2023

Valid to

30/10/2028

Scope:

The data have been provided by the seven ISO 14001 certified factories of Ravago Building Solutions producing these products in France, Germany, Greece, Hungary and the UK for the year 2021.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR
Independent verification of the declaration and data according to ISO 14025:2011
<input type="checkbox"/> internally <input checked="" type="checkbox"/> externally



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)



Mr Olivier Muller,
(Independent verifier)

Product

Product description/Product definition

RAVATHERM™ XPS and XPS X extruded polystyrene foams (XPS) are thermoplastic insulation foams produced according to EN 13164 Building insulation, EN 14307 Equipment insulation.

They are available in blue or grey board shape with a density range from 25 to 50 kg/m³. The boards can be delivered in various compressive strength values from 150 to 700 kPa.

To meet the need of various applications the boards are produced with different surfaces: with the extrusion skin, planed, grooved or with thermal embossing.

These XPS boards are supplied with different edge treatments such as butt edge, shiplap and tongue and groove. The EPD is related to unfaced XPS products only; Heat lamination of several XPS layers is included. Additional product treatment is not considered.

For the placing on the market of the construction product in the European Union/ European Free Trade Association (EU/EFTA) (with the exception of Switzerland) Regulation (EU) No. 305/2011 (CPR) applies. The product needs a declaration of performance taking into consideration the EN XPS standards (EN 13164 Building insulation, EN 14307 Equipment insulation).

For the application and use the respective national provisions apply.

Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to EN 13164:2012+A1:2015 - Thermal Insulation products for buildings EN 14307:2015 Thermal Insulation products for building equipment and industrial installations.

Base materials/Ancillary materials

RAVATHERMTM XPS and XPS X are mostly made of polystyrene (CAS 9003-53-6), blown with carbon dioxide and non-halogenated co-blown agents altogether up to 8 % by weight in relation to the material input.

Basic material Mass portion

Polystyrene 89 - 93 %

Blowing agents 5 - 8 %

.Carbon Dioxide 55 - 75 %

.Co-blown Agents 25 - 45 %

Flame retardant 0 - 2 %

Additives (e.g. pigments) Less than 1%

Information that the product does not contain substances listed in the Candidate List of substances of very high concern (REACH Regulation) exceeding 0.1%: This product contains substances listed in the candidate list (date:17.01.2023) exceeding 0.1 percentage by mass: no

This product contains other Carcinogenic, Mutagenic, Reprotoxic (CMR) substances in categories 1A or 1B which are not on the candidate list, exceeding 0.1 percentage by mass: no

Biocide products were added to this construction product or it has been treated with biocide products (this then concerns a treated product as defined by the Regulation (EU) No 528/2012 on biocidal products): no

Reference service life

The durability of XPS foam is normally at least as long as the lifetime of the building/equipment in/with which it is used or at least 50 years. This is explained by the superior mechanical and water resistance properties of this product.

Application

The variety of the performance properties of RAVATHERM XPS and XPS X thermal insulation foams make them suitable for use in a large number of applications such as: perimeter insulation, inverted insulation for terrace roofs, insulation of pitched roofs, floor insulation including insulation of highly loaded industrial floors, insulation of thermal bridges for exterior walls, External Thermal Insulation Composite System (ETICS), insulation of cavity walls, agricultural building ceiling insulation, prefabricated elements e.g. building sandwich panels, insulation for building equipment and industrial installations (pipe sections, ...).

Technical Data

Acoustic properties are not relevant for XPS foams.

For fire performance, these products usually achieve the fire classification Euroclass E according to EN 13501-1.

Constructional data

Name	Value	Unit
Gross density	25 - 50	kg/m ³
Compressive strength acc. to EN 826	0.2 - 0.7	N/mm ²
Tensile strength acc. to EN 826	0.2 - 1	N/mm ²
Modulus of elasticity acc. to EN 826	10 - 50	N/mm ²
Calculation value for thermal conductivity EN 12667 and EN 13164 Annex C	0.03 - 0.035	W/(mK)
Water vapour diffusion resistance factor acc. to EN 12088	50 - 250	-
Creep behaviour or permanent compressive strength acc. to EN 1606	=< 0.25	N/mm ²
Water absorption after diffusion acc. to EN 12088	1 - 3	Vol.-%
Freeze-thaw resistance acc. to EN 12091	=< 1	Vol.-%

LCA: Calculation rules

Declared Unit

The declared unit is 1 m³ of the XPS insulation product. The declared product reflects the average of seven of Ravago's sites weighted by production volume share:

- Balaton (HU): 33.07 kg/m³ (18%)
- Rheinmuenster (DE): 34.75 kg/m³ (18%)
- Lavrion (GR): 33.60 kg/m³ (17%)
- Schkopau (DE): 35.23 kg/m³ (17%)
- Drusenheim (FR): 35.35 kg/m³ (16%)
- Artix (FR): 33.63 kg/m³ (9%)
- King's Lynn (GB): 38.08 kg/m³ (5%)

The weighted average density of the product is 34.4 kg/m³.

Declared unit

Name	Value	Unit
Gross density	34.4	kg/m ³
Declared unit	1	m ³

For XPS products with densities or thicknesses different from the reference density of 34.4 kg/m³, the environmental impacts may be calculated by linear scaling using the following formula.

$$I_{adap} = I_{ref} \times \frac{\rho_{adap}}{\rho_{ref}} \times \frac{d_{adap}}{d_{ref}}$$

Iadap – adapted LCIA indicator or LCI parameter

Iref – LCIA indicator or LCI parameter for reference density of 34.4 kg/m³

padap – adapted density

pref – reference density of 34.4 kg/m³

dadap – adapted board thickness

dref – thickness of reference board

System boundary

Type of EPD according to EN 15804: "cradle to gate with options, modules C1–C4, and module D". The following

modules are declared: A1–A3, C, D and additional modules: A4 + A5.

Production - Modules A1-A3

The product stage includes:

- Raw material supply including secondary materials (A1)
- Transport to the manufacturer (A2): Transport is considered for all the input raw materials
- Manufacturing (A3), including provision of all materials, products and energy, as well as waste processing up to the end-of-waste state.

Construction stage - Modules A4-A5

The construction process stage includes:

- Transport to the construction site (A4)
- Treatment of packaging material (A5)

End-of-life stage– Modules C1-C4 and D

The end-of-life stage includes

- Manual dismantling (Load free) (C1)
- Transport to EoL (C2)
- Waste processing & disposal (C) with two 100 % scenarios (scenario 1: Incineration (C3 and D); scenario 2: Landfill (C4))
- Reuse, recovery or recycling potential (D) - beyond system boundary.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are taken into account.

Background database: Sphera LCA FE (GaBi ts), CUP 2022.2

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

Information on describing the biogenic Carbon Content at factory gate

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.00375	kg C

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

The following technical scenario information is required for the declared modules and optional for non-declared modules.

The following technical information is a basis for the declared modules or can be used for developing specific scenarios in the context of a building assessment if modules are not declared (MND). The values refer to the declared unit of 1 m³ XPS

Transport to the building site (A4)

Name	Value	Unit
Litres of fuel (per declared unit - 1m3)	0.2	l/100km
Transport distance (weighted average based on production volumes)	495	km
Capacity utilisation (including empty runs)	61	%
Gross density of products transported	34.4	kg/m ³

The transport distance can be modified to project-specific criteria if required by linear scaling.

Installation into the building (A5)

The thermal treatment of the packaging is considered in this module. The following quantities are produced per 1 m³ of XPS product (weighted average based on production volume

shares):

Name	Value	Unit
Packaging film (LDPE)	0.68	kg
EPS Beams	0.29	kg
Wooden Pallet	0.01	kg

The transport to End of Life (C2) is calculated with a distance of 50 km (with 70 % utilization).

Name	Value	Unit
Collected separately waste type XPS	34.4	kg
Energy recovery (Scenario 1)	34.4	kg
Landfilling (Scenario 2)	34.4	kg

End of life (C1-C4)

For the End-of-Life stage, two different scenarios are considered. One scenario with 100 % incineration (scenario 1: C3/1, D1) and one scenario with 100 % landfill (scenario 2: C4/2, D2) are calculated. The incineration of XPS results in benefits beyond the system boundary (module D) due to energy substitution of electricity and thermal energy under European conditions.

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Module D includes the credits of the thermal and electrical energy generated in Modules A5 and C3/1 due to thermal treatment of packaging and product waste (XPS product). Avoided burdens have been calculated by the inversion of residual grid and thermal energy from natural gas, using European datasets.

A waste incineration plant with R1-value > 0.6 is assumed.

LCA: Results

The following tables display the environmentally relevant results according to EN 15804 for 1 m³ XPS board. The two EoL Scenarios are represented in modules C3/1, C4/2, D/1, and D/2. C3/1 and D/1 show the environmental results in the case of thermal treatment of XPS products. D/1 covers also the results of the packaging treatment from Module A5. Module C4/2 reflects the landfilling of XPS (for scenario 2, "landfilling" the values in Module D for XPS are 0). Hence, Module D/2 shows only the environmental results of the packaging treatment from Module A5.

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage						End of life stage			Benefits and loads beyond the system boundaries		
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m³ RAVATHERM™ XPS product

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3/1	C4/2	D/1	D/2
GWP-total	kg CO ₂ eq	9.38E+01	3.01E+00	3.11E+00	0	2.79E-01	1.15E+02	2.44E+00	-3.68E+01	-1.56E+00
GWP-fossil	kg CO ₂ eq	9.38E+01	2.98E+00	3.1E+00	0	2.77E-01	1.15E+02	2.44E+00	-3.68E+01	-1.56E+00
GWP-biogenic	kg CO ₂ eq	3.13E-02	1.27E-02	8.17E-03	0	1.18E-03	3.44E-03	5.14E-03	-4.42E-02	-1.88E-03
GWP-luluc	kg CO ₂ eq	2.85E-02	1.68E-02	3.42E-06	0	1.56E-03	1.35E-04	1.19E-03	-1.61E-03	-6.81E-05
ODP	kg CFC11 eq	1.94E-10	1.8E-13	1.33E-13	0	1.67E-14	4.82E-12	3.27E-12	-1.79E-10	-7.6E-12
AP	mol H ⁺ eq	1.47E-01	2.97E-03	2.99E-04	0	2.76E-04	1.01E-02	7.22E-03	-3.71E-02	-1.57E-03
EP-freshwater	kg P eq	1.5E-04	8.98E-06	3.11E-08	0	8.33E-07	1.13E-06	4.55E-04	-9.21E-06	-3.91E-07
EP-marine	kg N eq	3.82E-02	9.38E-04	6.37E-05	0	8.7E-05	2.22E-03	1.6E-03	-1.18E-02	-4.99E-04
EP-terrestrial	mol N eq	4.18E-01	1.13E-02	1.4E-03	0	1.05E-03	4.75E-02	1.75E-02	-1.28E-01	-5.41E-03
POCP	kg NMVOC eq	2.28E-01	2.57E-03	1.89E-04	0	2.39E-04	6.54E-03	5.14E-03	-3.39E-02	-1.44E-03
ADPE	kg Sb eq	1.47E-05	2.51E-07	3.23E-09	0	2.33E-08	1.17E-07	1.69E-07	-3.03E-06	-1.29E-07
ADPF	MJ	2.81E+03	4.02E+01	3.6E-01	0	3.73E+00	1.28E+01	3.46E+01	-6.83E+02	-2.9E+01
WDP	m ³ world eq deprived	1.69E+01	2.7E-02	2.78E-01	0	2.5E-03	0	-2.4E-02	-1.4E+00	-5.94E-02

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential)

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m³ RAVATHERM™ XPS product

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3/1	C4/2	D/1	D/2
PERE	MJ	9.9E+01	2.29E+00	2.2E-01	0	2.12E-01	3.06E+00	2.84E+00	-5.64E+01	-2.39E+00
PERM	MJ	1.35E-01	0	-1.35E-01	0	0	0	0	0	0
PERT	MJ	9.91E+01	2.29E+00	8.52E-02	0	2.12E-01	3.06E+00	2.84E+00	-5.64E+01	-2.39E+00
PENRE	MJ	1.48E+03	4.03E+01	4.32E+01	0	3.74E+00	1.3E+03	3.46E+01	-6.83E+02	-2.9E+01
PENRM	MJ	1.33E+03	0	-4.29E+01	0	0	-1.28E+03	0	0	0
PENRT	MJ	2.81E+03	4.03E+01	3.6E-01	0	3.74E+00	1.28E+01	3.46E+01	-6.83E+02	-2.9E+01
SM	kg	9.48E+00	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0
FW	m ³	4.68E-01	2.58E-03	6.5E-03	0	2.4E-04	2.2E-01	4.47E-04	-8.6E-02	-3.65E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m³ RAVATHERM™ XPS product

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3/1	C4/2	D/1	D/2
HWD	kg	1.52E-07	1.93E-10	3.38E-11	0	1.79E-11	1.2E-09	5.33E-09	-8.23E-08	-3.49E-09
NHWD	kg	7.61E-01	5.77E-03	1.42E-02	0	5.36E-04	6.62E-01	3.42E+01	-1.61E-01	-6.84E-03
RWD	kg	5.51E-02	4.96E-05	2.17E-05	0	4.6E-06	7.7E-04	4.25E-04	-6.38E-02	-2.71E-03

CRU	kg	0	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	0	0
MER	kg	0	0	0	0	0	0	0	0	0
EEE	MJ	3.64E-01	0	6.33E+00	0	0	2.08E+02	0	0	0
EET	MJ	6.48E-01	0	1.13E+01	0	0	3.71E+02	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional: 1 m³ RAVATHERM™ XPS product

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3/1	C4/2	D/1	D/2
PM	Disease incidence	1.13E-06	1.75E-08	1.75E-09	0	1.62E-09	5.9E-08	6.94E-08	-3.24E-07	-1.38E-08
IR	kBq U235 eq	8.34E+00	7.27E-03	3.56E-03	0	6.75E-04	1.26E-01	6.27E-02	-9.33E+00	-3.96E-01
ETP-fw	CTUe	1.61E+03	2.79E+01	1.69E-01	0	2.59E+00	6.26E+00	3.38E+01	-1.2E+02	-5.09E+00
HTP-c	CTUh	3.24E-08	5.62E-10	1.9E-11	0	5.22E-11	6.31E-10	1.52E-09	-4.47E-09	-1.89E-10
HTP-nc	CTUh	1.42E-06	2.91E-08	5.99E-10	0	2.7E-09	2.05E-08	1.27E-07	-2.05E-07	-8.7E-09
SQP	SQP	1.12E+02	1.38E+01	1.09E-01	0	1.28E+00	3.88E+00	2.49E+00	-3.58E+01	-1.52E+00

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

References

Standards

CPR

Regulation No. 305/2011: Construction Products Regulation of the European Parliament and of the European Council, 2011.

EN 12088

EN 12088:2013-06 Thermal insulating products for building applications. Determination of long term water absorption by diffusion

EN 12091

EN 12091:2013-06 Thermal insulating products for building applications - Determination of freeze-thaw resistance

EN 12667

EN 12667:2001 Thermal performance of building materials and products - Determination of thermal resistance by means of guarded hot plate and heat flow meter methods - Products of high and medium thermal resistance

EN 13164 + A1

EN 13164:2012 + A1:2015 Thermal insulation products for buildings - Factory-made extruded polystyrene foam (XPS) products - Specification

EN 13501

EN 13501-1:2019-05 Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations Type III environmental declarations — Principles and procedures.

EN 14307

EN 14307:2015 Thermal insulation products for building equipment and industrial installations - Factory-made extruded polystyrene foam (XPS) products - Specification

EN 1606

EN 1606:2013-05 Thermal insulating products for building applications - Determination of compressive creep

REACH

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

BPR

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products

EN 15804

EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations - Core rules for the product category of construction products.

Further References

GaBi ts

GaBi ts dataset documentation for the software-system and databases, LBP, University of Stuttgart and thinkstep, Leinfelden-Echterdingen, 2023 (<https://www.gabi-software.com/support/gabi>)

IBU 2021

Institut Bauen und Umwelt e.V.: General Instructions for the



EPD programme of Institut Bauen und Umwelt e.V., Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021
(www.ibu-epd.com)

PCR Part A

PCR - Part A: Calculation rules for the Life Cycle Assessment and Requirements on the Background Report, version 1.3,

Institut Bauen und Umwelt e.V., 2021.

PCR Part B

PCR - Part B: Requirements of the EPD for Insulating materials made of foam plastics, v8, Institut Bauen und Umwelt e.V., 2023.

Publisher



Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Programme holder



Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Author of the Life Cycle Assessment



Sphera Solutions GmbH
Hauptstraße 111- 113
70771 Leinfelden-Echterdingen
Germany

+49 711 341817-0
info@sphera.com
www.sphera.com

Owner of the Declaration



RBS Germany GmbH
Value Park Y51
06258 Schkopau
Germany

-
info.de.rbs@ravago.com
www.ravagobuildingsolutions.com