



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15333-10-1011

Lino Fertigboden


Product group: Linoleum



ZIPSE GmbH & Co. KG / ZIRO
Tullastraße 26
79341 Kenzingen



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



Contents

 SHI Product Assessment 2024	1
 QNG - Qualitätssiegel Nachhaltiges Gebäude	2
 DGNB New Construction 2023	3
 DGNB New Construction 2018	4
Product labels	5
Legal notices	6
Technical data sheet/attachments	7

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Wood-based floor coverings	TVOC $\leq 300 \mu\text{g}/\text{m}^3$ Formaldehyd $\leq 36 \mu\text{g}/\text{m}^3$	Indoor Air Quality Certified
Valid untill: 19 March 2027			



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.3 Multi-layer wood parquet, bamboo coverings, and floor coverings on wood-based panels	VOC / Emissions / hazardous substances	QNG ready
Verification: Herstellerdeklaration vom 20.03.2025			



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	47c Wood-based materials in floor coverings	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: Herstellerdeklaration vom 20.03.2025

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	47c Floor coverings for indoor use (with wooden components)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: Herstellerdeklaration vom 20.03.2025



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	47a Industrially manufactured products	Formaldehyde	Quality level 4
Verification: Herstellerdeklaration vom 20.03.2025			



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



The IBU ("Institut Bauen und Umwelt e.V.") is an initiative of building product manufacturers committed to sustainability in construction. It serves as the programme operator for Environmental Product Declarations (EPDs) in accordance with the EN 15804 standard. The IBU EPD programme provides comprehensive life cycle assessments and environmental impact data for construction products, supported by independent third-party verification.



Product:

Lino Fertigboden

SHI Product Passport no.:

15333-10-1011



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu




lino klick

Stand: Juni 2024

Linoleum-Boden zum Klicken mit HDF-Trägerplatte



Technische Daten	
Dielen-Format	620 x 450 x 10 mm
Kartoninhalt	6 Dielen/1,68 m ²
Paletteninhalt	60 Kartons/100,80 m ²
Oberfläche	X-trem finish Versiegelung
Auflage	2,0 mm zweischichtiges Linoleum
Träger	6,8 mm HDF
Gegenzug	1,2 mm Presskork-Trittschalldämmung
Kantenbearbeitung	Glatte Kante
Verlegeart	Leimlose UNICLIC-Technik
Prüfwerte	
Antistatisch (EN 1815)	< 2 kV
Beanspruchungsklasse (EN 685)	23/32
Brandverhalten (EN-ISO 9239-1)	Cfl-s1 • Gibt bei Verbrennung keine toxischen Gase ab
Chemikalieneinwirkung (EN 423)	Beständig gegen verdünnte Säuren, Öle, Fette etc.
Feuchtraumeignung	Nein
Flächengewicht (EN 430)	8.600 g/m ²
Fußbodenheizungsgeeignet	Ja (Warmwasser-Fußbodenheizung)
Resteindruck (EN 433)	0,12 mm
Rutschhemmung (DIN 51130 • EN 13893)	DIN = R 10 • EN = DS > 0,30
Stuhlrolleneignung (EN 425 • EN 12529)	Ja, mit Rollen-Typ W
Trittschallwert (EN-ISO 717-2 • DIN 52210-030 E1-T-PFLD)	16 dB
Wärmedurchgangswiderstand (DIN-EN 52612-Teil 1)	0,098 m ² x K/W
Zigarettenglutbeständigkeit (EN 1399)	Ja
Entsorgung	Hausmüll oder Second Life





lino plus

Der robuste Linoleum-Fertigfußboden mit der extra starken Kork-Trittschalldämmung.



Technische Daten	
Dielen-Format	930 x 460 x 10 mm
Kartoninhalt	4 Dielen/1,712 m ²
Paletteninhalt	60 Kartons/102,72 m ²
Oberfläche	Acryl-Polish Behandlung, marmorierte Optik
Auflage	2,0 mm zweischichtiges Linoleum
Träger	6,8 mm HDF
Gegenzug	1,2 mm Presskork-Trittschalldämmung
Kantenbearbeitung	4-seitig gefast
Verlegeart	Leimlose UNICLIC-Technik
Prüfwerte	
Antistatisch (EN 1815)	< 2 kV
Beanspruchungsklasse (EN 685)	23/32
Brandverhalten (EN-ISO 9239-1)	Cfl-S1
Chemikalieneinwirkung (EN 423)	Beständig gegen verdünnte Säuren, Öle, Fette etc.
Feuchtraumeignung	Nein
Flächengewicht (EN 430)	8.600 g/m ²
Fußbodenheizungsgeeignet	Ja (Warmwasser-Fußbodenheizung)
Resteindruck (EN 433)	0,12 mm
Rutschhemmung (DIN 51130 • EN 13893)	DIN = R 9 • EN = DS > 0,30
Stuhlrolleneignung (EN 425 • EN 12529)	Ja, mit Rollen-Typ W
Trittschallwert (DIN 52210-030 E1-T-PFLD)	16 dB
Wärmedurchgangswiderstand (DIN-EN 52612-Teil 1)	0,098 m ² x K/W
Zigarettenglutbeständigkeit (EN 1399)	Ja
Entsorgung	Hausmüll oder Second Life



MADE IN EUROPE

