



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15060-10-1013

REWASI TOP UV+

Product group: Underlay Membranes - Underside sheathing membrane - Waterproofing membranes



BWK Dachzubehör GmbH
Birkirchstraße 1
74549 Wolpertshausen



Product qualities:



Köttner
Helmut Köttner
Scientific Director
Freiburg, 02 February 2026



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



Contents

■ SHI Product Assessment 2024	1
■ QNG - Qualitätssiegel Nachhaltiges Gebäude	2
■ DGNB New Construction 2023	3
■ DGNB New Construction 2018	4
■ BNB-BN Neubau V2015	5
■ EU taxonomy	6
■ BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other products	TVOC ≤ 300 µg/m ³ Formaldehyd ≤ 24 µg/m ³	Indoor Air Quality Certified

Valid until: 19 September 2026



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



■ QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment

Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt			Not relevant for assessment



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control		Substances according to Annex C	EU taxonomy compliant

Verification: Herstellererklärung vom 16.01.2025



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality			Not relevant for assessment



Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:

REWASI TOP UV+

SHI Product Passport no.:

15060-10-1013



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzinger Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

TECHNISCHES DATENBLATT

REWASI TOP UV+ 150



Beschreibung/ Anwendung

Diffusionsoffene 3-lagige Unterdeckbahn bestehend aus zwei wasserabweisenden Polypropylen-Spinnvlies Lagen die eine Linopore UV+ Spezial-Funktionsmembran einbetten. Auch zur direkten Verlegung auf Holzschalung oder Wärmedämmung. Auch mit doppelter Selbstklebekante (2-fach SK) lieferbar*.

Technische Daten

Eigenschaft	Prüfung	Einheit	Wert	
Anwendung:	-	-	Unterdeckbahn/ Unterspannbahn	
Funktionsschicht:	-	-	Linopore UV+ Spezial-Funktionsmembran	
Trägermaterial:	-	-	Polypropylen-Spinnvlies	
Flächengewicht:	EN 1849-2	g/ m ²	150	
Dicke:	EN 1849-2	mm	0,7	
Maßhaltigkeit:	EN 1107-2	%	<1	
Brandverhalten:	EN 13501-1	Klasse	E	
Widerstand gegen Wasserdurchgang:	EN 1928	Klasse	W 1	
Wert nach künstlicher Alterung:	EN 1297/1296	Klasse	W 1	
Zugfestigkeit/ Höchstzugkraft längs:	EN 12311-1	N/ 50 mm	310	
Zugfestigkeit/ Höchstzugkraft quer:	EN 12311-1	N/ 50 mm	300	
Höchstzugkraftdehnung längs:	EN 12311-1	%	55	
Höchstzugkraftdehnung quer:	EN 12311-1	%	35	
Weiterreißwiderstand/ Nagelschaft längs:	EN 12310-1	N/ 200 mm	190	
Weiterreißwiderstand/ Nagelschaft quer:	EN 12310-1	N/ 200 mm	200	
Werte nach künstlicher Alterung:	EN 1297/1296	%	>75 des Neuwertes	
Erhöhte Anforderung zur künstlichen Alterung:	EN 1297/1296	°C	+100	
Kaltbiegeverhalten:	EN 1109	°C	-40	
Wasserdampfdurchlässigkeit:	EN ISO 12572	s _d -Wert-m	0,06	
Widerstand gg. Luftdurchgang:	EN 12114	m ³ / (m ² /h/50Pa)	<0,1	
Temperaturbeständigkeit:	EN13859-1	°C	-40 bis +100	
UV-Beständigkeit:	-	Monate	>3	
Widerstand gegen Schlagregen:	TU Berlin	-	bestanden	
Eignung als Werkstoff für Behelfsdeckung:	-	-	8 Wochen mit Naht- und Perforationssicherung	
ZVDH-Produktdatenblatt – Klasse:	-	-	UDB-A / USB-A/ Klasse 6 - 3	
Entspricht Ö-Norm – Tab. 5 u. 6/ Anwendung:	B3661/ 4119		UD do-k/ Regensicheres Unterdach – Ö-Norm	
DTU 40.29/ 31.2 France	-	cm	60	
CSTB – Zertifikat:	-	-	17-004	
Bahnbreite:	EN 1848-2	m	1,50*	3,0
Rollenlänge:	EN 1848-2	m	50	50
Rollengewicht:	-	kg	12	20
VPE:	-	Rollen/ m ²	28 Rollen/ 2100m ²	15 Rollen/ 2250 m ²
Art.-Nr.: (ohne SK / mit SK):	10000 6475/ 6478			

Hinweis:

Sämtliche Angaben beruhen auf dem aktuellen Stand unserer Erfahrungen zum Zeitpunkt der Erstellung. Gegebenenfalls sind diese bei Bedarf/ Änderungen anzupassen. Änderungen vorbehalten. Werte/ Leistungen zu den wesentlichen Eigenschaften gemäß EN/ Verarbeitungshinweise siehe aktuelle Technische Daten/ Verarbeitungsanleitung/-Hinweise/ LE-Dop. Die Werte können Toleranzen unterliegen. Ohne Angabe gilt die branchenübliche Toleranz gemäß Norm, Material und Eigenschaft. Es gelten unsere allgemeinen Verkaufs- und Lieferbedingungen.

	BWK-Dachzubehör GmbH Birkichstraße 1 D – 74549 Wolpertshausen	07 / LE-Dop 647564787214 NB 0799 – CPR : KIWA GR DIN EN 13859-1/-2 20230522
--	---------------------------------------------------------------------	---------------------------------------------------------------------------------------------



VERARBEITUNGSHINWEISE

REWASI TOP UV+ 150

Verarbeitung

REWASI TOP ist eine diffusionsoffene Unterdeckbahn, die direkt auf Wärmedämmung oder Holzschalung verlegt werden kann. Die Naht- und Stoßausbildung kann je nach Anwendungsfall verklebt oder lose überlappend ausgeführt werden. **REWASI TOP** wird in der Regel von unten beginnend mit ca. 10 cm Überdeckung (Überlappungsmarkierung-SK) direkt auf die Holzschalung bzw. parallel zur Traufe spannungsfrei und ohne Durchhang zwischen den Sparrenfeldern verlegt. Die Fixierung der Unterdeckbahn erfolgt Zug um Zug mit Tacker und Konterlatte. Fixierungen in der Fläche sind zu überkleben/ abzudichten. Eine zusätzliche Abdichtung z.B. mit Nageldichtmaterial* zwischen Konterlatte und **REWASI TOP** wird empfohlen. **REWASI TOP** ist verdeckt im Überdeckungsbereich zu befestigen. Bei Unterschreitung der Regeldachneigung ist die Zusatzmaßnahme mindestens gemäß der Fachregeln des Deutschen Dachdeckerhandwerks oder nach den nationalen Vorgaben auszuführen. Über den First hinweg erfolgt die Verlegung der Unterdeckbahn mit einer Überlappung von 30 cm. Bei ungedämmten Spitzböden muss für ausreichende Belüftung gesorgt werden, **REWASI TOP** sollte in diesem Fall nicht über den First gezogen werden.

Die Behebung kleiner Beschädigungen und das Abkleben der Stoß- und Überdeckungsfugen müssen mit Spezialklebebändern* aus unserem Lieferprogramm erfolgen. Großflächige Beschädigungen an der Unterdeckbahn mit Originalfolienzuschnitten und Spezialklebstoffen* ausbessern.

REWASI TOP Unterdeckbahnen sind wasserabweisend ausgerüstet, dennoch kein Deckungsmaterial für den dauerhaften Außeneinsatz und sobald wie möglich einzudecken.

Vor der Eindeckung wird eine Kontrolle der Befestigungen/ Verklebungen und der Bahnoberfläche auf evtl. entstandene Beschädigungen durch äußerliche Einflüsse empfohlen und wenn erforderlich, ist die Reparatur und entsprechende Nacharbeit vor der weiteren Verarbeitung auszuführen.

Für eine ordnungsgemäße Funktion der Unterdeckbahn ist der gesamte Dachaufbau nach den z. Zt. geltenden Fachregeln sowie nach den darin enthaltenen Merkblättern, herausgegeben vom Zentralverband des Deutschen Dachdeckerhandwerks e.V. Köln, auszuführen.

Lagerung

REWASI TOP - Rollen dürfen bei Einlagerung über einen längeren Zeitraum weder direktem Sonnenlicht noch der Witterung ausgesetzt werden. Die Stapelung der Paletten übereinander ist zu vermeiden.

Systemzubehör*:

Anwendung für:	Überlappung		Beschädigungen	Durchdringungen/ Durchnagelungen	Anschlüsse
	Längs	Quer/Stoß			
SK-Selbstklebekante	X				
Thermo - Tape/ SOLID Tape UNI		O	X		
Thermo - Nageldichtband				X	O
Thermo - Kleb + Dicht	O	X	X		X
Thermo - Flex				X	
Thermo Butyl				X	X

X = Standardanwendung O = Optionale Anwendung (auch abhängig vom Untergrund)



Bestätigung – Herstellererklärung: D_24354_1_23334_1_AB2484_Upgrade_SHI

Die BWK Produkte:

**DIFFLEX ALLROUND ND, DIFFLEX THERMO TPU ND, REWASI TOP UV+, SOLID FOLIENKLEBER,
SOLID SD 2, SOLID TAPE UNI, SOLID VARIUS**

erfüllen die Vorgaben der ECHA/ REACH, das Material ist frei von ökologisch/ gesundheitlich bedenklichen/ zu vermeidenden Stoffen, wie:

SVHC-Stoffe, VOC-Stoffe, CMR-Stoffe Kategorie 1A / 1B, Blei-, Cadmium-, und zinnorganischen Verbindungen, Lösungsmittel, Chlorparaffine, Polybromierte Biphenyle (PBB), Polybromierte Diphenylether (PBDE), Phosphorsäureester (TCEP): Gehalt = < 0,1% und frei von Stoffen mit z.B. diesen Auswirkungen, →also nicht:

- ✚ krebsfördernd, erbgutverändernd und fortpflanzungsgefährdend (CMR)
- ✚ persistent, bioakkumulierend und toxisch (PBT)
- ✚ sehr persistent und sehr bioakkumulierend (vPvB) sowie
- ✚ besorgniserregend (z. B. endokrine Disruptoren)

Zusammenfassend:

Die o.g. Produkte haben die Emissions-Prüfkammeruntersuchungen mit sehr guten Ergebnissen durchlaufen, sind gemäß den Materialien, der bestimmungsgemäßen Verwendung und Recyclingfähigkeit als nachhaltig anzusehen und auch für Flora und Fauna, Menschen (Anwender und Bewohner) auch gesundheitlich und ökologisch unbedenklich.

BWK Dachzubehör ◊ TA-Technische Abteilung ◊ Rainer Floßmann, 16.01.2025

Hinweis:

Sämtliche Angaben beruhen auf dem aktuellen Stand unserer technischen Erfahrungen zum Zeitpunkt der Erstellung. Gegebenenfalls sind diese bei Bedarf etwaigen Veränderungen anzupassen. Technische Änderungen vorbehalten.
Es gelten unsere allgemeinen Verkaufs- und Lieferbedingungen.

BWK-Dachzubehör GmbH
Birkichstraße 1
D – 74549 Wolpertshausen

