



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

15176-10-1002

ESCO 3 Schicht Parkett

Product group: Parquet

esco[®]
Enchanted
by oak

ESCO CZ PRODUCTION s.r.o.
Blatenska 267
387 31 Radomysl



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



Contents

■ SHI Product Assessment 2024	1
■ QNG - Qualitätssiegel Nachhaltiges Gebäude	2
■ DGNB New Construction 2023	3
■ DGNB New Construction 2018	4
■ BNB-BN Neubau V2015	5
■ EU taxonomy	6
■ BREEAM DE Neubau 2018	7
Product labels	8
Legal notices	9
Technical data sheet/attachments	10

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Wood-based floor coverings	TVOC $\leq 300 \mu\text{g}/\text{m}^3$ Formaldehyd $\leq 36 \mu\text{g}/\text{m}^3$	Indoor Air Quality Certified
Valid untill: 01 October 2026			



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco® Enchanted
by oak

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.3 Multi-layer wood parquet, bamboo coverings, and floor coverings on wood-based panels	VOC / Emissions / hazardous substances	QNG ready
Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024			



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco®
Enchanted
by oak

DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	Assessment
EC02.6 Climate resilience (*)	May positively contribute to the overall building score

Criteria	Quality level
ENV1.3 Responsible resource extraction	May positively contribute to the overall building score

Verification: PEFC Zertifikaat

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	47c Wood-based materials in floor coverings	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	47c Floor coverings for indoor use (with wooden components)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 4

Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024.



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco[®] Enchanted
by oak

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	47a Industrially manufactured products	Formaldehyde	Quality level 4

Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024.



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco[®] Enchanted
by oak

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	2b Wood-based floor coverings – also systems	VOC / hazardous substances	Quality level 3

Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024 und SDB für die Beschichtungen (Grundierung + Endbeschichtung)



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco® Enchanted
by oak

EU taxonomy

The EU Taxonomy classifies economic activities and products according to their environmental impact. At the product level, the EU regulation defines clear requirements for harmful substances, formaldehyde and volatile organic compounds (VOCs). The Sentinel Holding Institut GmbH labels qualified products that meet this standard.

Criteria	Product type	Considered substances	Assessment
DNSH - Pollution prevention and control	Floor coverings (including associated adhesives and sealants)	Substances according to Annex C, formaldehyde, carcinogenic VOCs category 1A/1B	EU taxonomy compliant
Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024. Bestätigung REACH vom 20.03.2025.			



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco® Enchanted
by oak

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Flooring materials (including floor levelling compounds and resin flooring)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality

Verification: eurofins Prüfbericht Nr. 392-2024-00382601_A_EN vom 01.10.2024.



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco® Enchanted
by oak

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



Product:

ESCO 3 Schicht Parkett

SHI Product Passport no.:

15176-10-1002

esco[®] Enchanted
by oak

Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/C3%BCfverfahren/C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

DECLARATION OF CONFORMITY



3 LAYER FLOORING

Tested by Eurofins Product Testing and evaluated against:

French VOC Regulation



Degree of March 2011 (DEVL1101903D) and Arrêté of April 2011 (DEVL1104875A)

modified in February 2012 (DEVL1133129A)

French CMR components

Pass

Regulation of April and May 2009 (DEVP0908633A and DEVP0910046A)

Italian CAM Edilizia

Pass

DM 23 giugno 2022 n. 256, GURI n.183 del 6 agosto 2022

ABG/AgBB

Pass

Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)

Belgian Regulation

Pass

Royal decree of May 2014 (C-2014/24239

Indoor Air Comfort

Pass

Indoor Air Comfort 9.0 of June 2023

Indoor Air Comfort Gold

Pass

Indoor Air Comfort GOLD 9.0 of June 2023

BREEAM International

Exemplary level

BREEAM International New Construction v6.0 (2021)

BREEAM NOR

Exemplary level

BREEAM-NOR v6.1 New Construction (2023)

EU Taxonomy

Pass

Regulation (EU) 2020/852 of the European Parliament and of the Council

LEED v4.1 BETA (outside U.S.)

Pass

LEED v4.1 BETA for Building Design and Construction (February2024)

Test report: 392-2024-00383601_A_EN

DECOSPAN
Wood Solutions



CERTIFICATE

TÜV SÜD Czech s.r.o.

Product Certification Body No 3084,
accredited by ČIA according to ČSN EN ISO/IEC 17065:2013
approves that company

esco

— A DECOSPAN COMPANY —

ESCO CZ PRODUCTION s.r.o.

Blatenská 267

CZ – 387 31 Radomyšl

proved the conformity of the Chain of Custody System
with the requirements of PEFC ST 2002:2020 and PEFC ST 2001:2020
identical with the TD CFCS 2002:2020 and TD CFCS 2001:2020

with the following scope:

**Solid oak floors, three layer oak floors and two layer oak floors, oak
sawn wood, oak sawlogs and veneer logs, sawdust, oak lamellas
CoC method: percentage method**

**Solid pine floors, Deciduous logs other than oak, Coniferous logs
CoC method: physical separation**

type of certification: individual



This certification is valid
from: **24.06.2021** till: **23.06.2026**

Certificate No.: TSUD-PEFC-COC-000002, revision 1

The list of products according to the PEFC product categories to which this certificate applies is given in the
annex to this certificate, which is an integral part of it and contains 1 page.

Place and date of issue: Prague, 19.06.2024



Pavla Nerandžičová



The certification relates only to the scope described in this document. The certificate validity is subject to regular surveillance.
Revision No.1 of the TSUD-PEFC-COC-000002 certificate replaces the previous issue of the TSUD-PEFC-COC-000021 and
was issued due to a change in the scope of certificate and the product categories


TUV®

Product categories:
010100 Sawlogs and veneer logs
010300 Chips and particles
030102 Solid wood boards and planks
030107 Other sawnwood
090205 Floor

3-Schicht Fussboden 11mm



KONSTRUKTION



VERFÜGBARE KOLLEKTIONEN

Kollektion	Chateau	Kotonial	Soft Tone	Harfa Vintage	Pelgrim	Karel IV
Oberfläche behandlung	geschliffen	gebürstet	leicht gebürstet	unregelmäßig sägerau, gebürstet	speziell gekittet & gealtert	handgefertigt
Behandlung	Osmo PolyX + Osmo PolyX top-coating					ESCO oxidativ ÖL
	Landhausediele					
Verbindung	N&F					
Fase	4V					
Länge(mm)	20% qm 680-1200, 80% qm 1720+ max. 2400 mm, bis zu 20% gestossen					
Dimension	Sortierung					
155	Lively	✓	✓			

TECHNISCHE EIGENSCHAFTEN

	Test Methode	Anforderung	Leistung
Charakteristiken, Konformitätsbeurteilung und CE Kennzeichnung	EN 14342, EN 13489		umgesetzt
Holzfeuchtigkeit	ČSN EN 13183-1		7 ±2%
Freisetzung von Formaldehyd	ČSN EN 717-1	≤ 0,124mg/m3	E1
Gehalt an PCP	CEN/TR 14823	≤ 5 ppm	entspricht
Gleitwiderstand geschliffen	CEN/TS 15676		trocken ≥ 69, nass ≥ 26
Gleitwiderstand gebürstet	CEN/TS 15676		trocken ≥ 69, nass ≥ 29
Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten	ČSN EN 13501-1		Dfl-S1
Wärmedurchlassleitwiderstand	ČSN EN ISO 10456		0,085 m2 · K/W
Wärmeleitfähigkeit	ČSN EN ISO 10456		0,13 W/mK
Biologische Beständigkeit	ČSN EN 335		Klasse 1
Fussbodenheizung			✓

Empholene Nutzung	Geeignet für den Innenbereich in allen Projektbereichen: Wohnen, Gewerbe, Gastgewerbe, Einzelhandel. Es gelten die aktuellen Garantie- und Wartungsanweisungen
Nachhaltig bewirtschaftete Wälder	Dieses Produkt besteht aus PEFC-zertifiziertem Holz

Tested by Eurofins Product Testing and evaluated against:

French VOC Regulation		Degree of March 2011 (DEV1.1101903D) and April of April 2011 (DEV1.1104875A) modified in February 2012 (DEV1.113129A)
French CMR components	Pass	Regulation of April and May 2009 (DEV0906033A and DEV0910046A)
Italian CAM Edilizia	Pass	DM 23 giugno 2022 n. 256, GURI n.183 del 6 agosto 2022
ABG/AgBB	Pass	Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)
Belgian Regulation	Pass	Royal decree of May 2014 (C-201424239)
Indoor Air Comfort	Pass	Indoor Air Comfort 9.0 of June 2023
Indoor Air Comfort Gold	Pass	Indoor Air Comfort GOLD 9.0 of June 2023
BREEAM International	Exemplary level	BREEAM International New Construction v6.0 (2021)
BREEAM NOR	Exemplary level	BREEAM-NOR v6.1 New Construction (2023)
EU Taxonomy	Pass	Regulation (EU) 2020/852 of the European Parliament and of the Council
LEED v4.1 BETA (outside U.S.)	Pass	LEED v4.1 BETA for Building Design and Construction (February 2024)

Test report: 302-2024-0030301_A_EN



Promoting Sustainable Forest Management




Wood Solutions

3-Schicht Fussboden 14mm



KONSTRUKTION



VERFÜGBARE KOLLEKTIONEN

Kollektion	Chateau	Kolonial	Soft Tone	Harfa Vintage	Pelgrim	Karel IV
Oberfläche behandlung	geschliffen	gebürstet	leicht gebürstet	unregelmäßig sägerau, gebürstet	speziell gekittet & gealtert	handgefertigt
Behandlung	Osmo PolyX + Osmo PolyX top-coating					ESCO oxidativ Öl
	Landhausediele					
Verbindung	N&F					
Fase	2V, 4V optionell					
Länge(mm)	20% qm 680-1200, 80% qm 1720+ max. 2400 mm, bis zu 20% gestossen					
Dimension	Sortierung					
190	Special rustic	✓	✓	✓	✓	
	Original	✓	✓	✓	✓	
	Calm	✓	✓	✓	✓	✓
	Superb	✓	✓	✓	✓	✓
	Elegance	✓	✓	✓	✓	✓
	Karel IV					✓
225	Special rustic	✓	✓	✓	✓	
	Original	✓	✓	✓	✓	
	Superb/Elegance	✓	✓	✓	✓	✓
245	Special rustic		✓	✓	✓	
	Original		✓	✓	✓	
	Superb/Elegance		✓	✓	✓	
	Fischgrät					
Verbindung	N&F					
Fase	4V, ohne Fase optionell					
100/120x600	Special rustic	✓	✓	✓	✓	
175x700	Original	✓	✓	✓	✓	
	Superb/Elegance	✓	✓	✓	✓	✓
	Chevron					
Verbindung	N&F					
	Eingesetzte Feder an den kurzen Seiten					
Schnittwinkel	45°					
Fase	4V					
100x600	Original	✓	✓	✓	✓	
	Superb/Elegance	✓	✓	✓	✓	

TECHNISCHE EIGENSCHAFTEN

	Test Methode	Anforderung	Leistung
Charakteristiken, Konformitätsbeurteilung und CE Kennzeichnung	EN 14342, EN 13489		umgesetzt
Holzfeuchtigkeit	ČSN EN 13183-1		7 ±2%
Freisetzung von Formaldehyd	ČSN EN 717-1	≤ 0,124mg/m3	E1
Gehalt an PCP	CEN/TR 14823	≤ 5 ppm	entspricht
Gleitwiderstand geschliffen	CEN/TS 15676		trocken ≥ 69, nass ≥ 26
Gleitwiderstand gebürstet	CEN/TS 15676		trocken ≥ 69, nass ≥ 29
Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten	ČSN EN 13501-1		Dfl-S1
Wärmedurchlassleitwiderstand	ČSN EN ISO 10456		0,11 m² · K/W
Wärmeleitfähigkeit	ČSN EN ISO 10456		0,13 W/mK
Biologische Beständigkeit	ČSN EN 335-1, ČSN EN 335-2		Klasse 1
Fussbodenheizung			✓ bis Breite 225 mm

Empholene Nutzung

Geeignet für den Innenbereich in allen Projektbereichen: Wohnen, Gewerbe, Gastgewerbe, Einzelhandel. Es gelten die aktuellen Garantie- und Wartungsanweisungen

Nachhaltig bewirtschaftete Wälder

Dieses Produkt besteht aus PEFC-zertifiziertem Holz

Tested by Eurofins Product Testing and evaluated against:

French VOC Regulation



Degree of March 2011 (DEVL1101903D) and Amélie of April 2011 (DEVL1104875A) modified in February 2012 (DEVL1133129A)

French CMR components

Pass

Regulation of April and May 2009 (DEVP0008633A and DEVP0910046A)

Italian CAM Edilizia

Pass

DM 23 giugno 2002 n. 256, GURI n.183 del 6 agosto 2002

ABG/AgBB

Pass

Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)

Belgian Regulation

Pass

Royal decree of May 2014 (C-2014/24239)

Indoor Air Comfort

Pass

Indoor Air Comfort 9.0 of June 2023

Indoor Air Comfort Gold

Pass

Indoor Air Comfort GOLD 9.0 of June 2023

BREEAM International

Exemplary level

BREEAM International New Construction v6.0 (2021)

BREEAM NOR

Exemplary level

BREEAM-NOR v6.1 New Construction (2023)

EU Taxonomy

Pass

Regulation (EU) 2020/852 of the European Parliament and of the Council

LEED v4.1 BETA (outside U.S.)

Pass

LEED v4.1 BETA for Building Design and Construction (February 2024)


Test report: 362-2024-0630001_A_EN



3-Schicht Fussboden 15mm



KONSTRUKTION



VERFÜGBARE KOLLEKTIONEN

Kollektion	Chateau	Kolonial	Soft Tone	Harfa Vintage	Pelgrim	Karel IV
Oberfläche behandlung	geschliffen	gebürstet	leicht gebürstet	unregelmäßig sägerau, gebürstet	speziell gekittet & gealtert	handgefertigt
Behandlung	Osmo PolyX + Osmo PolyX top-coating					ESCO oxidativ Öl
	Landhausediele					
Verbindung	N&F					
Fase	2V, 4V optionell					
Länge(mm)	20% qm 680-1200, 80% qm 1720+ max. 2400 mm, bis zu 20% gestossen					
Dimension	Sortierung					
190	Special rustic	✓	✓	✓	✓	
	Original	✓	✓	✓	✓	
	Calm					
	Superb	✓	✓	✓	✓	✓
	Elegance	✓	✓	✓	✓	✓
	Karel IV					
225	Special rustic	✓	✓	✓	✓	
	Original	✓	✓	✓	✓	
	Superb/Elegance	✓	✓	✓	✓	✓
245	Special rustic		✓	✓	✓	
	Original		✓	✓	✓	
	Superb/Elegance		✓	✓	✓	✓

TECHNISCHE EIGENSCHAFTEN

	Test Methode	Anforderung	Leistung
Charakteristiken, Konformitätsbeurteilung und CE Kennzeichnung	EN 14342, EN 13489		umgesetzt
Holzfeuchtigkeit	ČSN EN 13183-1		7 ±2%
Freisetzung von Formaldehyd	ČSN EN 717-1	≤ 0,124mg/m3	E1
Gehalt an PCP	CEN/TR 14823	≤ 5 ppm	entspricht
Gleitwiderstand geschliffen	CEN/TS 15676		trocken ≥ 69, nass ≥ 26
Gleitwiderstand gebürstet	CEN/TS 15676		trocken ≥ 69, nass ≥ 29
Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten	ČSN EN 13501-1		Cfl-S1
Wärmedurchlassleitwiderstand	ČSN EN ISO 10456		0,12 m² · K/W
Wärmeleitfähigkeit	ČSN EN ISO 10456		0,13 W/mK
Biologische Beständigkeit	ČSN EN 335-1, ČSN EN 335-2		Klasse 1
Fussbodenheizung			✓ bis Breite 225 mm

Empholene Nutzung

Geeignet für den Innenbereich in allen Projektbereichen: Wohnen, Gewerbe, Gastgewerbe, Einzelhandel. Es gelten die aktuellen Garantie- und Wartungsanweisungen

Nachhaltig bewirtschaftete Wälder

Dieses Produkt besteht aus PEFC-zertifiziertem Holz

Tested by Eurofins Product Testing and evaluated against:

French VOC Regulation		Degree of March 2011 (DEV11019030) and Amélie of April 2011 (DEV11104875A) modified in February 2012 (DEV11133129A)
French CMR components	Pass	Regulation of April and May 2009 (DEVP0908633A and DEVP0910046A)
Italian CAM Edilizia	Pass	DM 23 giugno 2002 n. 256, GURI n.183 del 6 agosto 2002
ABG/AgBB	Pass	Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)
Belgian Regulation	Pass	Royal decree of May 2014 (C-2014/24239)
Indoor Air Comfort	Pass	Indoor Air Comfort 9.0 of June 2023
Indoor Air Comfort Gold	Pass	Indoor Air Comfort GOLD 9.0 of June 2023
BREEAM International	Exemplary level	BREEAM International New Construction v6.0 (2021)
BREEAM NOR	Exemplary level	BREEAM-NOR v6.1 New Construction (2023)
EU Taxonomy	Pass	Regulation (EU) 2020/852 of the European Parliament and of the Council
LEED v4.1 BETA (outside U.S.)	Pass	LEED v4.1 BETA for Building Design and Construction (February 2024)


Test report: 392-2024-0030301_A_EN



3-Schicht Fussboden 20mm



KONSTRUKTION



VERFÜGBARE KOLLEKTIONEN

Kollektion	Chateau	Kolonial	Soft Tone	Harfa Vintage	Pelgrim	Karel IV
Oberfläche behandlung	geschliffen	gebürstet	leicht gebürstet	unregelmäßig sägerau, gebürstet	speziell gekittet & gealtert	handgefertigt
Behandlung	Osmo PolyX + Osmo PolyX top-coating					ESCO oxidativ Öl
Verbindung	Landhausediele					
Fase						
Länge(mm)						
Dimension						
190						
Sortierung						
Original						
Superb/Elegance						

TECHNISCHE EIGENSCHAFTEN

Charakteristiken, Konformitätsbeurteilung und CE Kennzeichnung	Test Methode	Anforderung	Leistung
Holzfeuchtigkeit	EN 14342, EN 13489		umgesetzt
Freisetzung von Formaldehyd	ČSN EN 13183-1		7 ±2%
Gehalt an PCP	ČSN EN 717-1	≤ 0,124mg/m3	E1
Gleitwiderstand geschliffen	CEN/TR 14823	≤ 5 ppm	entspricht
Gleitwiderstand gebürstet	CEN/TS 15676		trocken ≥ 69, nass ≥ 26
Klassifizierung von Bauprodukten und Bauarten zu ihrem Brandverhalten	CEN/TS 15676		trocken ≥ 69, nass ≥ 29
Wärmedurchlassleitwiderstand	ČSN EN 13501-1		Dfl-S1
Wärmeleitfähigkeit	ČSN EN ISO 10456		0,15 m² · K/W
Biologische Beständigkeit	ČSN EN ISO 10456		0,13 W/mK
Fussbodenheizung	ČSN EN 335-1, ČSN EN 335-2		Klasse 1
			✓

Empholene Nutzung

Geeignet für den Innenbereich in allen Projektbereichen: Wohnen, Gewerbe, Gastgewerbe, Einzelhandel. Es gelten die aktuellen Garantie- und Wartungsanweisungen

Nachhaltig bewirtschaftete Wälder

Dieses Produkt besteht aus PEFC-zertifiziertem Holz

Tested by Eurofins Product Testing and evaluated against:

French VOC Regulation		Degree of March 2011 (DEV1.1101903D) and Amis of April 2011 (DEV1.1104875A) modified in February 2012 (DEV1.1133129A)
French CMR components	Pass	Regulation of April and May 2009 (DEV1.0908633A and DEV1.0910046A)
Italian CAM Edilizia	Pass	DM 23 giugno 2022 n. 256, GURI n. 183 del 6 agosto 2022
ABG/AgBB	Pass	Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (June 2021)
Belgian Regulation	Pass	Royal decree of May 2014 (C-201424239)
Indoor Air Comfort	Pass	Indoor Air Comfort 9.0 of June 2023
Indoor Air Comfort Gold	Pass	Indoor Air Comfort GOLD 9.0 of June 2023
BREEAM International	Exemplary level	BREEAM International New Construction v6.0 (2021)
BREEAM NOR	Exemplary level	BREEAM-NOR v6.1 New Construction (2023)
EU Taxonomy	Pass	Regulation (EU) 2020/852 of the European Parliament and of the Council
LEED v4.1 BETA (outside U.S.)	Pass	LEED v4.1 BETA for Building Design and Construction (February 2024)

Test report: 392-2024-0030301_A_EN

