

## OAK PREMIUM WIDE PLANK



### PRODUCT DESCRIPTION

General:	Product consists of three layers: a noble oak surface layer, a middle layer made of pine slats and a bottom layer made of spruce veneer
Appearance:	Specially selected material with a delicate wood grain and subdued, uniform colouring. Small knots allowed only. Sapwood does not occur.
Pattern:	1-strips, Premium grade
Surface finishing:	Light or strong brush
Oil:	Saicos Hardwax Oil, Gloss 5-9, 30g/m <sup>2</sup>
Connecton system:	A Tongue-and-groove joint or a Vålinge Click 5G system
Hardness according to EN 13489:	Average hardness 37 MPa
Moisture content:	7% +/- 2%
Floor heating installation:	Yes, max. 27°

### DIMENSIONS & TOLERANCES (EN 13489)

Thickness (≤ 0.2mm):	15 or 14mm
Length (+/- 0.1%):	from 1080 to 3000mm (1080, 1600, 1800, 2000, 2200, 2400, 3000 mm)
Width (+/- 0.2mm):	from 140 to 300 mm (140, 160, 190, 250, 300 mm)

## TECHNICAL SPECIFICATIONS

Top layer:	4mm or 3mm oak
Middle layer:	9mm pine
Bottom layer:	2mm spruce veneer
Fire class:	Cfls-S1
Formaldehyde content:	E1, < LOD (264 h)
Thermal conductivity:	0,12 W/(m*K)
PCP content:	PCP < 5 x IO 6"
Slip resistance:	USRV58

## GRADING DESCRIPTION\*

Healthy knots:	Acceptable up to 5mm, sporadically
Unhealthy knots with filler:	Not allowed
Unhealthy knot holes:	Not allowed
Bark pockets:	Not allowed
Structure:	Varied
Colour:	Varied
Arrangement of fibres:	Varied
Silver grains:	Acceptable
Sapwood:	Not allowed
Middle and end cracks:	Not allowed
Heartwood:	Not allowed

\*Up to 3 % of the products may have a different grading than the described above according to EN 13489

## PRODUCT LABELLING

