

OAK STANDARD WIDE PLANK



PRODUCT DESCRIPTION

General:	Product consists of three layers: a noble oak surface layer, a middle layer made of pine slats and a bottom layer made of spruce veneer
Appearance:	The wood contains very few and small knots. Colour variation is controlled to the minimum. The finish will be clear, with virtually no major visible flaws.
Pattern:	1-strips, Standard grade
Surface finishing:	Light or strong brush
Oil:	Saicos Hardwax Oil, Gloss 5-9, 30g/m ²
Connecton system:	A Tongue-and-groove joint or a Välinge Click 5G system
Hardness according to EN 13489:	Average hardness 37 MPa
Moisture content:	7% +/- 2%
Floor heating installation:	Yes, max. 27°

DIMENSIONS & TOLERANCES (EN 13489)

Thickness ($\leq 0.2\text{mm}$):	15 or 14mm
Length (+/- 0.1%):	from 1800 to 2400mm (1800, 2000, 2200, 2400 mm)
Width (+/- 0.2mm):	190 mm

TECHNICAL SPECIFICATIONS

Top layer:	4mm or 3mm oak
Middle layer:	9mm pine
Bottom layer:	2mm spruce veneer
Fire class:	Cfls-S1
Formaldehyde content:	E1, < LOD (264 h)
Thermal conductivity:	0,12 W/(m*K)
PCP content:	PCP < 5 x IO 6"
Slip resistance:	USRV58

GRADING DESCRIPTION*

Healthy knots:	Acceptable up to 50mm
Unhealthy knots with filler:	Acceptable up to 30mm
Unhealthy knot holes:	Acceptable up to 15mm
Bark pockets:	Not allowed
Structure:	Varied
Colour:	Varied
Arrangement of fibres:	Varied
Silver grains:	Acceptable without limit
Sapwood:	Not allowed
Middle and end cracks:	Not allowed
Heartwood:	Not allowed

*Up to 3 % of the products may have a different grading than the described above according to EN 13489

PRODUCT LABELLING



www.blauer-engel.de/uz176