

OAK STYLE WIDE PLANK



PRODUCT DESCRIPTION

General:	Product consists of three layers: a noble oak surface layer, a middle layer made of pine slats and a bottom layer made of spruce veneer
Appearance:	Products are characterized by clear and contrasting grains, as well as visible knots and cracks. The putty used to fill in the cracks can be either lighter or darker in colour. The floor darkens under the influence of UV rays.
Pattern:	1-strip, Rustic grade
Surface finishing:	Light or strong brush
Oil:	Saicos Hardwax Oil, Gloss 5-9, 30g/m ²
Connecton system:	A Tongue-and-groove joint or a Vålinge Click 5G system
Hardness according to EN 13489:	Average hardness 37 MPa
Moisture content:	7% +/- 2%
Floor heating installation:	Yes, max. 27°

DIMENSIONS & TOLERANCES (EN 13489)

Thickness (≤ 0.2mm):	15 or 14mm
Length (+/- 0.1%):	from 1080 to 3000mm (1080, 1600, 1800, 2000, 2200, 2400, 3000 mm)
Width (+/- 0.2mm):	from 140 to 300 mm (140, 160, 190, 250, 300 mm)

TECHNICAL SPECIFICATIONS

Top layer:	4mm or 3mm oak
Middle layer:	9mm pine
Bottom layer:	2mm spruce veneer
Fire class:	Cfls-S1
Formaldehyde content:	E1, < LOD (264 h)
Thermal conductivity:	0,12 W/(m*K)
PCP content:	PCP < 5 x IO 6"
Slip resistance:	USRV58

GRADING DESCRIPTION*

Healthy knots:	Acceptable up to 80mm in diameter
Unhealthy knots with filler:	Acceptable up to 60mm in diameter
Unhealthy knot holes:	Acceptable up to 40mm in diameter
Bark pockets:	Acceptable
Structure:	Varied
Colour:	Varied
Arrangement of fibres:	Varied
Silver grains:	Acceptable without limit
Sapwood:	Not allowed
Middle and end cracks:	Acceptable
Heartwood:	Acceptable

*Up to 3 % of the products may have a different grading than the described above according to EN 13489

PRODUCT LABELLING

