



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

12049-10-1017

Vario MultiTape SL +

Product group: Sealing tapes



Saint-Gobain Isover G + H AG
Bürgermeister-Grünzweig-Straße 1
67059 Ludwigshafen



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



Product:

Vario MultiTape SL +

SHI Product Passport no.:

12049-10-1017



Contents

■ SHI Product Assessment 2024	1
■ QNG - Qualitätssiegel Nachhaltiges Gebäude	2
Product labels	3
Legal notices	4
Technical data sheet/attachments	5

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

Vario MultiTape SL +

SHI Product Passport no.:

12049-10-1017



SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Assessment
SHI Product Assessment		Indoor Air Quality Certified
Valid untill: 04 October 2026		



Product:

Vario MultiTape SL +

SHI Product Passport no.:

12049-10-1017



QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment



Product:

Vario MultiTape SL +

SHI Product Passport no.:

12049-10-1017



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Product:

Vario MultiTape SL +

SHI Product Passport no.:

12049-10-1017



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu



Vario MultiTape SL +

Klebeband mit geteiltem Abdeckstreifen für innen und außen

Anwendung

Zur Herstellung luftdichter Anschlüsse an Dachflächenfenster, Rohre und Ecken im Innen- und Außenbereich.

- ideal für schwierig verklebbare Innen- und Außenecken
- Abdeckstreifen in der Mitte geschlitzt und getrennt abziehbar
- integriertes Maßband
- passgenau und flexibel faltbar
- wasserbeständig



* Angaben über den Grad der Emission von flüchtigen Substanzen in der Raumluft, die ein toxisches Risiko beim Einatmen darstellen, auf einer Skala von A+ (sehr emissionsarm) bis C (hohe Emission)



Klebeband mit geteiltem Abdeckstreifen für innen und außen

Material

Modifiziertes Acrylat ohne Lösungsmittel, wasserbeständig Trägermaterial: Spezial-PE-Folie mit Verstärkungsgitter Abdeckmaterial (nur SL Version): Abdeckstreifen mittig geschlitzt

Verarbeitungshinweise

1. Zur sicheren Verarbeitung immer nur so viel Liner des Klebebands abziehen, wie gerade benötigt wird. Die beiden Liner nacheinander abziehen. 2. Das Klebeband gerade abschneiden, für leichtes Handling sorgt der praktische Maßbandaufdruck. 3. Abschließend alle Verklebungen mit einer planen Gummiwalze anrollen oder mit unserem ISOVER Vario Rakel glattstreichen und insbesondere die Kanten dabei fest andrücken.

Lagerungshinweis

trocken, kühl und vor UV-Strahlung schützen

Technische Eigenschaften				
Eigenschaften	Zeichen	Einheit	Kenngößen und Messwerte	Normen
Temperaturbeständigkeit	-	°C	-30 bis +100	-
Chemisches Verhalten	-	-	Frei von Lösungsmitteln, Isocyanaten, PVC, Schwermetallen und Halogenen.	-
UV-Beständigkeit	-	-	bis zu 6 Monate UV-beständig	-
Geeignete Untergründe	-	-	PE-, PA-, PU-, PP- und Alufolien, Kraftpapiere, Metalle, Kunststoffe, harte Holzwerkstoffe (OSB-, Spanplatten, etc.), Holz (z.B. KVH, BSH). Der Untergrund muss tragfähig, trocken, staub- und fettfrei sein.	-
Mechanische Eigenschaften	-	-	geprüfte Klebeverbindung inkl. Alterung	DIN 4108-11
Trägermaterial	-	-	Dual-Layer-Aufbau: Spezial-PE-Folie mit Verstärkungsgitter, Abdeckstreifen mittig geschlitzt	-
Verarbeitungstemperatur	-	°C	ab -10	-

Wasserdampf Diffusionswiderstandszahl ist dickenabhängig

Lieferformen DE				
Bestell-Nr.	lfdm/ Rolle	Rollen/ Paket	Pakete/ Palette	Breite mm
560084	25	10	80	60

Lieferung in praktischer Display-Verpackung.

Made in Germany