

HOYTECH PVC Flooring			Issue Date: 27/03/2026
No	Property	Method & Standard	Result
1	Floor Covering Type	ISO 10582	Heterogeneous PVC
2	Total Thickness	EN ISO 24346	±0.13mm
3	Wear Layer	EN ISO 24340	0.3mm/0.5mm
4	Dimensional Stability	ISO 23999	≤ 0.12%
5	Curling	ISO23999	≤ 1.2mm
6	Residual Indentation	ISO 24343-1	≤ 0.01mm
7	Light Stability	ISO 105-B02 Method 3	≥ 6
8	Castor Chair	ISO 4918	No Visible damage
9	Reaction to fire	EN 13501-1	Bfl-S1
10	Slip Resistance	DIN 51130	R10
11	Chemical Resistance	ISO 26987	Resistant
12	Squareness	ISO 24342	≤ 0.1mm
13	Straightness	ISO 24342	≤ 0.1mm
14	Click Tension Force	EN 684	≥ 125N/5cm
15	Peel Resistance	ISO 234345	≥ 75N/5cm
16	VOC emissions	AgBB/DIBt	Certified
17	REACH SVHC	REACH SVHC	< 0.10%
18	Phthalates	EN14372	< 0.10%
19	CMR 1A/1B		< 0.10%
20	Heavy Metal(Tin, Cadmium,Lead)		Do Not Contain
21	Chlorinated paraffins (SCCPs, MCCPs, LCCPs)		< 0.10%
22	CE marking	EN 14041	Certified
23	EPD	EN 15804, ISO 14025	Certified

