



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

14693-10-1009

b!design SPC 3.8/0.3

Product group: Design floors - Vinyl

b!design

b!design / BAUHAUS
Gutenbergstraße 21
68167 Mannheim



Product qualities:



Köttner

Helmut Köttner
Scientific Director

Freiburg, 02 February 2026



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009



Contents

 SHI Product Assessment 2024	1
 QNG - Qualitätssiegel Nachhaltiges Gebäude	2
 DGNB New Construction 2023	3
 DGNB New Construction 2018	4
 BNB-BN Neubau V2015	5
 BREEAM DE Neubau 2018	6
Product labels	7
Legal notices	8
Technical data sheet/attachments	9

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design

SHI Product Assessment 2024

Since 2008, Sentinel Holding Institut GmbH (SHI) has been establishing a unique standard for products that support healthy indoor air. Experts carry out independent product assessments based on clear and transparent criteria. In addition, the independent testing company SGS regularly audits the processes and data accuracy.

Criteria	Product category	Harmful substance limit	Assessment
SHI Product Assessment	Other floor coverings	TVOC $\leq 160 \mu\text{g}/\text{m}^3$ Formaldehyd $\leq 10 \mu\text{g}/\text{m}^3$	Indoor Air Quality Certified
Valid untill: 12 August 2027			



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design

QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	2.2 Resilient floor coverings – including multilayer systems	VOC / Emissions / hazardous substances / polycyclic aromatic hydrocarbons (PAH) / SVHC / heavy metals	QNG ready
Verification: Prüfberichte des Instituts Eco-Institut vom 1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001- L, 2) 55793-004, 3) 55793-003. Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt. Herstellererklärung vom 08.08.2025			



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009



DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	Assessment
SOC1.2 Indoor air quality (*)	May positively contribute to the overall building score
Verification: SHI Schadstoffgeprüft	

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	7 Floor coverings (Resilient floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 1
Verification: Prüfberichte des Instituts Eco-Institut vom1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001- L, 2) 55793-004, 3) 55793-003. Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt			

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	7 Floor coverings for indoor use (elastic floor coverings)	VVOCs, VOC, SVOC emissions and content of hazardous substances	Quality level 1
Verification: Prüfberichte des Instituts Eco-Institut vom1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001- L, 2) 55793-004, 3) 55793-003. Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt			



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design 

DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	7 Floor coverings (Resilient floor coverings)	VOC / SVOC / hazardous substances	Quality level 1
Verification: Prüfberichte des Instituts Eco-Institut vom 1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001- L, 2) 55793-004, 3) 55793-003. Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt			



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design 

BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	2a Elastic floor coverings – with and without bonded underlay or insulation layer	VOC / hazardous substances / heavy metals	Quality level 3

Verification: Prüfberichte des Instituts Eco-Institut vom 1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001-L, 2) 55793-004, 3) 55793-003.
Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt. Herstellererklärung vom 08.08.2025.



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design

BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Flooring materials (including floor levelling compounds and resin flooring)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality

Verification: Prüfbericht des Instituts Eco-Institut vom 1) 10.01.2022 2) 12.12.2020 3) 21.12.2020, Prüfbericht Nr. 1) 56870-A001- L, 2) 55793-004, 3) 55793-003.
Konformitätserklärung vom 28.08.2025 bestätigt die materielle Übereinstimmung mit dem geprüften Produkt. Herstellererklärung vom 08.08.2025.



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009

b!design 

Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



This product is SHI Indoor Air Quality certified and recommended by Sentinel Holding Institut. Indoor-air-focused construction, renovation, and operation of buildings is made possible by transparent and verifiable criteria thanks to the Sentinel Holding concept.



Product:

b!design SPC 3.8/0.3

SHI Product Passport no.:

14693-10-1009



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

Technische Daten <i>Specifications</i>		RIGID SPC	MAXI SPC RIGID	TILE SPC SQ	MULTILAYER ISO
Format <i>Size</i> (mm)		1220 x 181	1220 x 228	600 x 600	1220 x 182
Gesamtstärke <i>Total thickness</i> (mm)		3,8	4,8	4,8	6
Oberschicht <i>Top layer</i> (mm)		0,3	0,5	0,3	0,3
Vergütung <i>Coating</i>		UV	UV	UV	UV
Struktur <i>Surface</i>		Embossed <i>Classic</i>	IRE	Sand Stone	Embossed <i>Classic</i>
Gefaste Kanten <i>Bevelled edge</i>		Nein <i>No</i>	Ja <i>Yes</i>	Ja <i>Yes</i>	Ja <i>Yes</i>
Klick-System <i>Click-system</i>		I4F	I4F	I4F	Uniclic
Unterlagsmatte <i>Underlay mat</i>		Nein <i>No</i>	Nein <i>No</i>	Nein <i>No</i>	Ja <i>Yes</i>
1 Karton <i>Box</i>	Stück <i>Pieces</i>	10	8	8	8
	m ²	2,208	2,225	2,88	1,776
	Kg	16,43	21,23	22,03	18,7
1 Palette <i>Pallet</i>	Kartons <i>Boxes</i>	40	33	32	40
	m ²	88,32	73,425	92,16	71,04
	Kg	657	701	705	748
Rutschhemmstufe <i>Antislip category</i>	DIN 51130	R10	R10	R10	R10
Gleitverhalten <i>Slip resistance</i>	EN 14041	DS	DS	DS	DS
Resteindruck <i>Residual indentation</i>	EN 433	Erfüllt <i>Pass</i>	Erfüllt <i>Pass</i>	Erfüllt <i>Pass</i>	Erfüllt <i>Pass</i>
Thermische Widerstand (m ² K/W) <i>Thermal resistance</i>	R =	0,030	0,032	0,094	0,055
Chemikalienbeständigkeit <i>Chemical resistance</i>	EN 423	Gut <i>Good</i>	Gut <i>Good</i>	Gut <i>Good</i>	Gut <i>Good</i>
Trittschallreduktion <i>Sound reduction</i>	ISO 140-8	4 dB	5 db	4 db	18 db
Verschleissverhalten <i>Wear resistance</i>	EN 660-2	Gr. T	Gr. T	Gr. T	Gr. T
Brandverhalten <i>Flammability</i>	BS EN 13501	B _{fl} -s1	B _{fl} -s1	B _{fl} -s1	B _{fl} -s1
Formaldehyd <i>Formaldehyde</i>		E1	E1	E1	E1
Fussbodenheizung <i>Underflooring heating</i>	EN 649	Geeignet zu Verlegung auf elektrischer Fussbodenheizung <i>Suitable for laying on electrical underfloor heating systems</i>			
Nutzungsklasse <i>Utilization class</i>		23/31	23/34	23/33	23/31
Garantie <i>Warranty</i>	Wohnen <i>Residential</i>	25 Jahre <i>Years</i>	25 Jahre <i>Years</i>	25 Jahre <i>Years</i>	25 Jahre <i>Years</i>
	Gewerblich gering <i>Light commercial</i>	5 Jahre <i>Years</i>	–	–	10 Jahre <i>Years</i>
	Gewerblich <i>Commercial</i>	–	5 Jahre <i>Years</i>	5 Jahre <i>Years</i>	–



Sämtliche Abbildungen können farblich vom Originalprodukt abweichen.

TUNDRA PINIE

- ◇ Natürliche Holzoptik
- ◇ Formstabil, bis 400 m² durchgehend verlegen ohne Dehnfugen
- ◇ Wasserresistent
- ◇ Nur 3,8 mm Aufbauhöhe
- ◇ Nutzschicht 0,3 mm
- ◇ L 1220 x B 181 mm
- ◇ Kartoninhalt 10 Dielen = 2,21 m²
- ◇ Phthalate frei
- ◇ Einfach, schwimmend verlegt
- ◇ I4F Klick-Verbindung
- ◇ Emissionsarm (Zertifiziert A+)
- ◇ Geringe Aufbauhöhe
- ◇ Nutzungsklasse 23/31

Vor der Verlegen zu beachten:

- Mengenbedarf +10% der Fläche
- Unterboden sauber, hart, eben, stabil und fest
- Unebenheiten ausgleichen (max. 3 mm pro 1,2 m)
- Wichtig: Raumtemperatur = Bodentemperatur = Nutzungstemperatur 10°C bis 60°C

Bei der Verlegung zu beachten:

- Sofern Unterlagsmatte erforderlich: Druckfeste, ausschliesslich für Vinyl zugelassene verwenden (mindestens 400 kPa/m², 1,5 mm, nicht klebend)
- Auf Linolium, Holz/Holzstoffplatten: 0,2 mm PE Baufolie zur Entkoppelung zwingend erforderlich!
- Die Dielen müssen richtig eingeklickt sein
- Dehnfugen zu Wänden und feststehenden Gegenständen von 4-6 mm vorsehen
- Maximale Feldgröße 20 x 20 m

Artikel-Nr.	Facido-Nr.	Bezeichnung	EAN	Pack/PAL
ST-0354-17	106100192	b!design Rigid SPC, Tundra Pinie, 3,8 mm	7640165926154	40



Sämtliche Abbildungen können farblich vom Originalprodukt abweichen.

SWISS PINIE

- ◊ Natürliche Holzoptik
- ◊ Formstabil, bis 400 m² durchgehend verlegen ohne Dehnfugen
- ◊ Wasserresistent
- ◊ Nur 3,8 mm Aufbauhöhe
- ◊ Nutzschicht 0,3 mm
- ◊ L 1220 x B 181 mm
- ◊ Kartoninhalt 10 Dielen = 2,21 m²
- ◊ Phthalate frei
- ◊ Einfach, schwimmend verlegt
- ◊ I4F Klick-Verbindung
- ◊ Emissionsarm (Zertifiziert A+)
- ◊ Geringe Aufbauhöhe
- ◊ Nutzungsklasse 23/31

Vor der Verlegen zu beachten:

- Mengenbedarf +10% der Fläche
- Unterboden sauber, hart, eben, stabil und fest
- Unebenheiten ausgleichen (max. 3 mm pro 1,2 m)
- Wichtig: Raumtemperatur = Bodentemperatur = Nutzungstemperatur 10°C bis 60°C

Bei der Verlegung zu beachten:

- Sofern Unterlagsmatte erforderlich: Druckfeste, ausschliesslich für Vinyl zugelassene verwenden (mindestens 400 kPa/m², 1,5 mm, nicht klebend)
- Auf Linolium, Holz/Holzstoffplatten: 0,2 mm PE Baufolie zur Entkoppelung zwingend erforderlich!
- Die Dielen müssen richtig eingeklickt sein
- Dehnfugen zu Wänden und feststehenden Gegenständen von 4-6 mm vorsehen
- Maximale Feldgröße 20 x 20 m

Artikel-Nr.	Facido-Nr.	Bezeichnung	EAN	Pack/PAL
ST-2075-05	106100193	b!design Rigid SPC, Swiss Pinie, 3,8 mm	7640165926161	40



Sämtliche Abbildungen können farblich vom Originalprodukt abweichen.

ICEBERG PINIE

- ◇ Natürliche Holzoptik
- ◇ Formstabil, bis 400 m² durchgehend verlegen ohne Dehnfugen
- ◇ Wasserresistent
- ◇ Nur 3,8 mm Aufbauhöhe
- ◇ Nutzschicht 0,3 mm
- ◇ L 1220 x B 181 mm
- ◇ Kartoninhalt 10 Dielen = 2,21 m²
- ◇ Phthalate frei
- ◇ Einfach, schwimmend verlegt
- ◇ I4F Klick-Verbindung
- ◇ Emissionsarm (Zertifiziert A+)
- ◇ Geringe Aufbauhöhe
- ◇ Nutzungsklasse 23/31

Vor der Verlegen zu beachten:

- Mengenbedarf +10% der Fläche
- Unterboden sauber, hart, eben, stabil und fest
- Unebenheiten ausgleichen (max. 3 mm pro 1,2 m)
- Wichtig: Raumtemperatur = Bodentemperatur = Nutzungstemperatur 10°C bis 60°C

Bei der Verlegung zu beachten:

- Sofern Unterlagsmatte erforderlich: Druckfeste, ausschliesslich für Vinyl zugelassene verwenden (mindestens 400 kPa/m², 1,5 mm, nicht klebend)
- Auf Linolium, Holz/Holzstoffplatten: 0,2 mm PE Baufolie zur Entkoppelung zwingend erforderlich!
- Die Dielen müssen richtig eingeklickt sein
- Dehnfugen zu Wänden und feststehenden Gegenständen von 4-6 mm vorsehen
- Maximale Feldgröße 20 x 20 m

Artikel-Nr.	Facido-Nr.	Bezeichnung	EAN	Pack/PAL
ST-0170-17	106100194	b!design Rigid SPC, Iceberg Pinie, 3,8 mm	7640165926178	40

Herstellereklärung - HWZI1

Name: **HWZ Int. AG**

Adresse: **Untere Gründlistrasse 23, 6055 Alpnach Dorf, Schweiz**

erklärt in eigener Verantwortung, dass die an die Bauhaus gelieferten Produkte:

Bezeichnung

Original-Artikelnummer

b!Design SPC 3.5/0.2 (Eiche Polaris)

b!Design SPC 3.5/0.2

b!design SPC 3.8/0.3

b!Design SPC 3.8/0.2

b!Design SPC 4.0/0.3

b!design SPC 4.2/0.3, Uniclic

b!Design SPC Silent 4.8/0.3

b!Design SPC 6.5/0.5

Position & Bauproduktgruppe: 2.2 Elastische Bodenbeläge - auch mehrschichtige Systeme

Betrachtete Stoffe: VOC / Emissionen / gefährliche Stoffe / Polyzyklische Aromatische Kohlenwasserstoffe (PAK) / SVHC / Schwermetalle

QNG-Anforderungen: Einhaltung AgBB-Schema, Kautschukbeläge

Schadstoffvermeidung: krebserzeugende Nitrosamine $\leq 0,011$ mg/kg oder $\leq 0,0002$ mg/m³; PVC-Bodenbeläge: reproduktiontoxische Phalate $\leq 0,10$ %; keine Zinn-, Cadmium- und Bleistabilisatoren

Obenstehende Produkte erfüllen die Kriterien für Schadstoffvermeidung in Baumaterialien vorgegeben durch das Qualitätssiegel Nachhaltiges Gebäude (QNG).

Alpnach Dorf, 18.11.2025

Jaime Iglesias

