



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

2765-10-1027

PU-Schäume - 1K Pistolenschäume (Flexibler Schaum)

Product group: Construction chemicals - Construction Foam - PU foam - Polyurethane (PU)



fischerwerke GmbH & Co. KG
Klaus-Fischer-Straße 1
72178 Waldachtal



Product qualities:

BNB-BN
NEUBAU
V2015



BREEAM
DE NEUBAU
2018





SENTINEL HOLDING
INSTITUT



Köttner

Helmut Köttner
Scientific Director

Freiburg, 19 February 2026



Product:

**PU-Schäume - 1K Pistolenschäume (Flexibler
Schaum)**

SHI Product Passport no.:

2765-10-1027



Contents

 BNB-BN Neubau V2015	1
 BREEAM DE Neubau 2018	2
Product labels	3
Legal notices	4
Technical data sheet/attachments	5

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

PU-Schäume - 1K Pistolenschäume (Flexibler Schaum)

SHI Product Passport no.:

2765-10-1027



BNB-BN Neubau V2015

The Bewertungssystem Nachhaltiges Bauen (Assessment System for Sustainable Building) is a tool for evaluating public office and administrative buildings, educational facilities, laboratory buildings, and outdoor areas in Germany. The BNB was developed by the former Federal Ministry for the Environment, Nature Conservation, Building and Nuclear Safety (BMUB) and is now overseen by the Federal Ministry for Housing, Urban Development and Building (BMWSB).

Criteria	Pos. / product type	Considered substance group	Quality level
1.1.6 Risiken für die lokale Umwelt	33 Spray and mounting foams	Halogenated refrigerants / individual hazardous substances (formaldehyde)	Quality level 3

Verification: Sicherheitsdatenblatt vom 31.01.2025 (Druckdatum)



Product:

PU-Schäume - 1K Pistolenschäume (Flexibler Schaum)

SHI Product Passport no.:

2765-10-1027



BREEAM DE Neubau 2018

BREEAM (Building Research Establishment Environmental Assessment Methodology) is a UK-based building assessment system that evaluates the sustainability of new constructions, refurbishments, and conversions. Developed by the Building Research Establishment (BRE), the system aims to assess and improve the environmental, economic, and social performance of buildings.

Criteria	Product category	Considered substances	Quality level
Hea 02 Indoor Air Quality	Interior adhesives and sealants (including flooring adhesives)	Emissions: Formaldehyde, TVOC, TSVOC, carcinogens	Exemplary quality
Verification: EMICODE EC1+-Zertifikat vom 09.10.2025			



Product:

**PU-Schäume - 1K Pistolenschäume (Flexibler
Schaum)**

SHI Product Passport no.:

2765-10-1027



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



The EMICODE® label, awarded by the German manufacturers' association "GEV – Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e. V.", is primarily relevant for flooring installation materials. The EMICODE® EC1^{PLUS} label, as the premium class, sets significantly stricter emission limits than the other label variants.



Product:

**PU-Schäume - 1K Pistolenschäume (Flexibler
Schaum)**

SHI Product Passport no.:

2765-10-1027



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/kriterien%20of%20C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu

PUP 750 FLEX B2 #543453

Merkmal	Wert	Einheit	Prüfvorschrift / Bemerk.
Chemische Basis	1K Polyurethan		
Farbe	creme		
Inhalt	750	ml	
Klebfreizeit	ca. 10	min	
Schneidzeit (20 mm Durchmesser)	ca. 30	min	+ 20 °C/ 50 % RLF
Baustoffklasse	B2		DIN 4102
Schaumausbeute, freigeschäumt	bis zu 48	l	freigeschäumt
Lagerhaltbarkeit	15	Monate	bei 20 °C
Verarbeitungstemperatur (Umgebung)	-10 bis + 35	°C	Optimal: + 20 °C
Dosentemperatur	+ 5 bis + 35	°C	Optimal: + 20 °C
Temperaturbeständigkeit	- 40 bis + 90	°C	ausgehärteter Schaum
Wärmeleitfähigkeit (λ)	$\leq 0,036$	W/(m*K)	
Luftdurchlässigkeit	< 0.1	m ³ /[h*m*(daPa) ^{2/3}]	EN 1026 & EN 12114 bei 1050 Pa
Aushärtung	chemisch durch Reaktion mit Luftfeuchtigkeit		

Anwendungshinweise

Der fischer PUP 750 Flex Schaum ist ein flexibler luftdichter und hochwärmedämmender Polyurethanschaum für Passivhäuser.

Der PUP 750 Flex Schaum für luftdichte und thermisch gedämmte Anschlussfugen ist zu verarbeiten wie ein herkömmlicher PU-Schaum zum Abdichten und Montieren von Fenster- und Türrahmen sowie Fensterbänken, zum Ausschäumen von Hohlräumen, Dachausbauten, Rohrdurchführungen, Rollladenkästen, etc.. Der Schaum haftet auf allen üblichen Baumaterialien, ausgenommen Polyethylen, Polypropylen, Silikon, Teflon, Öle und Fette, o. ä.. Der ausgehärtete Schaum ist elastisch, verrottungsfest, feuchtigkeitsbeständig und alterungsbeständig (vor UV-Strahlung schützen). Die Untergründe müssen fest, sauber, staub- und fettfrei sein

Zu kalte Dosen vorsichtig im lauwarmen Wasserbad erwärmen. Niemals über 50 °C erhitzen, da sonst Berstgefahr. Zu heiße Dosen im Wasserbad abkühlen.

Gelegentliches Schütteln unterstützt den Temperatenausgleich. Soweit nicht anders angegeben gelten die Angaben bei Standardbedingungen von 23 °C und 50 % r. F. und nicht gealtertem Schaum. Bei gealtertem Schaum sinkt die Ausbeute um bis zu 30%. Hierbei verkürzt sich auch die Klebfrei- und Schneidzeit. **Dose vor Gebrauch gut schütteln!**

Weitere Informationen zum Umgang entnehmen Sie bitte dem Sicherheitsdatenblatt.

Die Informationen in diesem technischen Datenblatt und unsere anwendungstechnische Beratung in Wort und Schrift erfolgen nach bestem Wissen, sind jedoch nur unverbindliche Hinweise und keine Garantie im Sinne von § 443 BGB. Wir empfehlen vor Verwendung unserer Produkte die Eignung für den vorgesehenen Verwendungszweck zu prüfen. Aufgrund der Vielfalt der Anwendungsmöglichkeiten des einzelnen Produkts und den nicht einschätzbaren Gegebenheiten am Ort der Verarbeitung empfehlen wir darüber hinaus vor Verwendung die Verklebung zu erproben.

Denzlingen, 17. Dezember 2025

Bestätigung fischer Polyurethanschäume

Sehr geehrte Damen und Herren,

hiermit bestätigen wir, dass die unten genannten Polyurethanschäume dem Anforderungskatalog des Qualitätssiegel Nachhaltiges Gebäude (QNG) entsprechen. Diese Produkte sind frei von halogenierten Treibmitteln und Formaldehyd, ebenfalls liegt der Gehalt an TCEP und Chlorparaffinen < 0,1 %. Alle genannten Produkte besitzen Emicode EC1 Plus.

Freundliche Grüße

fischerwerke GmbH & Co. KG

EIN UNTERNEHMEN DER UNTERNEHMENSGRUPPE FISCHER

Abt. Chemisches Labor

i. V. M. Vogel

Dr. Martin Vogel

i. A. Y. Herbstritt

Yvonne Herbstritt

Firmendaten

Telefon +49 7666 902-0
Telefax +49 7666 902-2929
Website www.fischer.de
GLN 40 06209 00000 7
USt-IDNr. DE 144252337
Anschrift:
Otto-Hahn-Str. 15, 79211 Denzlingen

Sitz

Klaus-Fischer-Straße 1, 72178 Waldachtal,
Deutschland
Registergericht Stuttgart HRA440255
Komplementär:
fischerinternational Beteiligungs GmbH,
Wiener Straße 95, 2514 Traiskirchen,
Österreich
Landesgericht Wiener Neustadt FN 319271 t

Geschäftsführer

Professor E. h. Senator E. h. E. h.
Dipl.-Ing. (FH) Klaus Fischer
Andreas Voll (Vorsitzender)
Maximilian Bronner, Dr. Oliver Geibig,
Jürgen Grün, Christian Hasenest
Marc-Sven Mengis, Claudia Rothe,
Matthias Schneider, Holger Thrun

Bankverbindung

Baden-Württembergische Bank
BLZ 600 501 01, Kto. 4 903 000
IBAN DE98 6005 0101 0004 9030 00
SWIFT SOLADEST600



Art. Nr.	Neue Bezeichnung	Bild
563227	Monomerarmer PU-Schaum PU-P EVO 750 B2	
543453	Flexibler Pistolenschaum PUP Flex 750 B2	
53084	Premium Pistolenschaum PUP Pro 825 B2	
503259	Premium Pistolenschaum PUP Pro 500 B2	
539197	Pistolenschaum Profi PUP S 750 B2	
40302	Pistolenschaum PUP S 750 B2	
539163	Pistolenschaum Profi PUP S 500 B2	
45300	Pistolenschaum schwer entflammbar PUP HF 750 B1	
513763	Brunnenschaum PUP BS 750 B2	
53080	Premium Schnellmontage- & Brunnenschaum PU Pro 750 B2	
50426	Premium Schnellmontage- & Brunnenschaum PU Pro 500 B2	
40301	Schnellmontageschaum Profi PU S 750 B2	
40300	Schnellmontageschaum PU S 500 B2	
506671	Perimeterklebeschaum PUP P 750 B2	
539164	WDVS Klebeschaum PUP WDVS 750	
53081	Schnellschaum Türzarge & Wanne PU 2K 400 B2	



Instytut Techniki Budowlanej

Badania naukowe | Prace rozwojowe | Akredytowany Zespół Laboratoriów |
Jednostka notyfikowana nr 1488 | Członek EOTA | Certyfikowane systemy zarządzania ISO 9001, ISO 27001

CLASSIFICATION No 01605/22/Z00NZM

Customer fischerwerke GmbH & Co. KG

Address Klaus-Fischer-Straße 1
72178 Waldachtal

Product Polyurethane foam
fischer PUP Flex 750 B2

CONSTRUCTION MATERIALS ENGINEERING DEPARTMENT of ITB
having conducted adequate tests, hereby confirms that
polyurethane foam fischer PUP Flex 750 B2 have the following properties:

Range of test		Classification* "fischer PUP Flex 750 B2"	Norm classification
Property	Test method		
Air permeability (1200 Pa)	PN-EN 1026:2001	class 4	PN-EN 12207:2001
Air permability coefficient, a $m^3/(m \cdot h \cdot daPa^{2/3})$	PN-EN 1026:2001	$a < 0,1$	-
Watertightness	PN-EN 1027:2001 met. 1A	E1200	PN-EN 12208:2001

*Classification relates to gaps of a width of 25 mm, filled with foam on the surface of at least 68 mm

Detailed results of the tests and information about the test sample are included
in Test Report LZM01 06052/16/R41NZM

Person responsible for test:

Head of CONSTRUCTION
MATERIALS ENGINEERING
DEPARTMENT

Magdalena Wasiak MsC, Eng

Ewa Sudoł PhD, Eng

Warsaw, 07/08/2022

This document shall cease to be valid in the event of changing the product components and/or the technology.
Classification is not a marketing authorisation.

ZAKŁAD INŻYNIERII MATERIAŁÓW BUDOWLANYCH

Warszawa | ul. Ksawerów 21

| tel. 22 56 64 409

| materiały@itb.pl

Instytut Techniki Budowlanej : 00-611 Warszawa | ul. Filtrowa 1 | tel. 22 825 04 71 | fax 22 825 52 86 | Dyrektor tel. 22 825 28 85 | 22 825 13 03 | fax 22 825 77 30 | KRS: 0000158785 | Regon: 000063650 | NIP: 525 000 93 58 | | www.itb.pl | instytut@itb.pl

**Gemeinschaft Emissionskontrollierte
Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.**

Association for the Control of Emissions from Products
for Flooring Installation, Adhesives and Building Materials



Awarding of licence for the use of EMICODE

Licence Number: 12585/03.08.15
For the product PUP FLEX 750 B2
Due to application date 30.10.2020

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM119 09.10.2025
valid until 09.10.2030

A handwritten signature in blue ink, appearing to read 'D. J. ...'.

The Secretary General
Association for the Control of Emissions in Products
for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Council of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in chapter 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not actively added to the product during manufacture (for exemptions see chapter 3.1.2.2 of the “GEV Classification Criteria”).
- The testing of the product is performed in accordance with the “GEV Testing Method”. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 ^{PLUS}	EC 1	EC 2
	max. allowed concentration [$\mu\text{g}/\text{m}^3$]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	≤ 1	≤ 1	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Formaldehyde after 28 days	≤ 10	≤ 10	≤ 10
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	< 10	< 10	< 10
Any volatile C1A/C1B after 28 days	< 1	< 1	< 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 ^{PLUS}	EC 1	EC 2
	max. allowed concentration [$\mu\text{g}/\text{m}^3$]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 400 thereof max. 100 SVOC
R value based on German AgBB LCI (NIK) after 28 days	≤ 1	≤ 1	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Formaldehyde after 28 days	≤ 10	≤ 10	≤ 10
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	< 10	< 10	< 10
Any volatile C1A/C1B after 28 days	< 1	< 1	< 1