Product Information



tesa® Powerstrips Poster

BNR 58003, 58066, 58126, 58213, 58303

Product Features

- · Posters can be replaced or rearranged, leaving both surface and poster undamaged
- Secure hold of up to 200g*
- Removable without trace thanks to the Powerstrips® technology
- Usable even on sensitive surfaces like wallpaper or varnished surfaces
- Due to special shape, ideal for light and sensitive materials etc.

Product Description

Self-adhesive tesa Powerstrips Poster are the ideal means to attach posters to the wall without causing any damage to the wall and the poster itself.

Application Fields

Step by step - How to apply:1. Clean the surface with alcohol or silicone-free glass cleaner

- 2. Apply the Powerstrip Poster strip on the object press for 5 seconds minimum
- 3. Fix object onto surface press for 5 seconds minimum
- 4. Make sure the tab can be accessed for removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Total thickness	400 μm
•	Holding power of strip up to	0.2 Kg			

Properties/Performance Values

 Ageing resistance (U 	V) yes	 Ozone resistance 	yes
 Application temperar 	ture 15 °C	 Residue free removal 	yes
 Applicationfield 	Kitchen, Living	 Solvent free 	yes
	room, Children's	 Suitable surfaces 	Even wood, Tiles,
	room, Office, Ha	ıll	Most plastics, Glass,
 Area of use 	Indoor		Acrylic glass, Steel
 Chemical resistance 	no	 Temperature resistance max. 	35 °C
 Hazard material 	no	 Temperature resistance min. 	5 °C
 Humidity resistance 	no	 UV resistant 	no
 Oil and grease resist 	ance no	 Waterproof 	no

^{*}Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Product Information



tesa® Powerstrips Poster

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

