



SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

14884-10-1017

tesamoll Türbodendoppeldichtung

Product group: Accessories & Tools



tesa SE
Hugo-Kirchberg-Straße 1
22848 Norderstedt



Product qualities:



Köttner

Helmut Köttner
Scientific Director
Freiburg, 02 February 2026



Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



Contents

■ QNG - Qualitätssiegel Nachhaltiges Gebäude	1
■ DGNB New Construction 2023	2
■ DGNB New Construction 2018	3
Product labels	4
Legal notices	5
Technical data sheet/attachments	6

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar





Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



QNG - Qualitätssiegel Nachhaltiges Gebäude

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment



Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment



Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



DGNB New Construction 2018

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment



Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.



Product:

tesamoll Türbodendoppeldichtung

SHI Product Passport no.:

14884-10-1017



Legal notices

(*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfverfahren/Pr%C3%BCfverfahren%20f%C3%BCr%20Produkte>

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Publisher

Sentinel Holding Institut GmbH
Bötzingen Str. 38
79111 Freiburg im Breisgau
Germany
Tel.: +49 761 590 481-70
info@sentinel-holding.eu
www.sentinel-holding.eu



tesamoll® Door-to-floor double-roll

Product Information

BNR 5418

Product Description

The tesamoll® Door-to-Floor Double Roll is a non-adhesive and removable instant draught stopper for doors that is able to seal gaps of up to 22 mm.

Product Features

- Suitable for smooth flooring surfaces like parquet, wooden or tile floors without a (or just with a very low) doorsill
- Suitable for interior use
- Suitable for gaps of up to 22mm
- Suitable for door leaf thicknesses up to 40 mm
- No adhesive

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------|----------------------|-------|
| • Type of adhesive | none | • Gap coverage up to | 22 mm |
|--------------------|------|----------------------|-------|

Properties/Performance Values

- | | | | |
|------------------------|---|----------------|-----|
| • Chemical resistance | no | • Reusable | yes |
| • Material | Polyester, LDPE (Low-density polyethylene), PE (polyethylene) | • Solvent free | yes |
| • Residue free removal | yes | | |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=05418>



tesamoll® Door-to-floor brush for textiles

Product Information

BNR 5403

Product Description

tesamoll® STANDARD Door-to-floor Brush for Textiles is an effective draught excluder brush that works perfectly even in combination with deep-pile carpets.

Product Features

- For deep-pile carpets
- For gaps of up to 15mm
- Extra long, elastic brush
- Easy self-adhesive fitting without screws or nails
- UV-resistant
- Abrasion-resistant
- Long-lasting and durable
- Durability: 6 years
- Material: plastic

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|----------------|-------|
| • Type of adhesive | acrylic | • Gap coverage | 15 mm |
|--------------------|---------|----------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|---------|------------------------|-----|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 6 years | • Solvent free | yes |



tesamoll[®] Door-to-floor brush for textiles

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05403>



tesamoll® COMFORT Door Brush

Product Information

BNR 5405

Product Description

The tesamoll® COMFORT Door-to-floor Brush is a self-adhesive door sealing brush that is ideal to save energy and protect your living room from cold draft.

Product Features

- Active levelling by integrated spring-loaded brush
- Ensures a perfect seal, even on tiled and uneven floors
- For gaps of up to 15mm
- Material: lacquered aluminium
- Easy self-adhesive fitting without screws or nails
- UV-resistant
- Durability: 8 years
- Abrasion-resistant
- Long-lasting and durable

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|----------------|-------|
| • Type of adhesive | acrylic | • Gap coverage | 15 mm |
|--------------------|---------|----------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|---------------------|------------------------|-----|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 8 years | • Solvent free | yes |
| • Material | Lacquered aluminium | | |



tesamoll® COMFORT Door Brush

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05405>



tesamoll® STANDARD Door Brush

Product Information

BNR 5433, 5433

Product Description

tesamoll® STANDARD Door-to-floor Brush is a highly effective self-adhesive draught excluder brush. It keeps cold air out and is able to seal gaps up to 12 mm.

Product Features

- Suitable for smooth floor surfaces like parquet and wooden floors, PVC, laminate
- For gaps of up to 12mm
- Easy self-adhesive fitting without screws or nails
- Durability: 4 years
- UV-resistant
- Abrasion-resistant
- Long-lasting and durable
- Material: plastic

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|----------------|-------|
| • Type of adhesive | acrylic | • Gap coverage | 12 mm |
|--------------------|---------|----------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------|---------|------------------------|-----|
| • Chemical resistance | no | • Residue free removal | no |
| • Durability | 4 years | • Solvent free | yes |
| • Material | Plastic | | |



tesamoll® STANDARD Door Brush

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05433>