



# SHI PRODUCT PASSPORT

Find products. Certify buildings.

SHI Product Passport No.:

**14884-10-1027**

## tesamoll® Premium Flexible, transparent

Product group: Window accessories



tesa SE  
Hugo-Kirchberg-Straße 1  
22848 Norderstedt



### Product qualities:



*Köttner*  
Helmut Köttner  
Scientific Director  
Freiburg, 02 February 2026

Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**



# Contents

■ QNG - Qualitätssiegel Nachhaltiges Gebäude	1
■ DGNB New Construction 2023	2
■ DGNB New Construction 2018	3
Product labels	4
Legal notices	5
Technical data sheet/attachments	6

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**



## ■ **QNG - Qualitätssiegel Nachhaltiges Gebäude**

The Qualitätssiegel Nachhaltiges Gebäude (Quality Seal for Sustainable Buildings), developed by the German Federal Ministry for Housing, Urban Development and Building (BMWSB), defines requirements for the ecological, socio-cultural, and economic quality of buildings. The Sentinel Holding Institut evaluates construction products in accordance with QNG requirements for certification and awards the QNG ready label. Compliance with the QNG standard is a prerequisite for eligibility for the KfW funding programme. For certain product groups, the QNG currently has no specific requirements defined. Although classified as not assessment-relevant, these products remain suitable for QNG-certified projects.

Criteria	Pos. / product group	Considered substances	QNG assessment
3.1.3 Schadstoffvermeidung in Baumaterialien	not applicable	not applicable	QNG ready - Not relevant for assessment

Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**


## ■ DGNB New Construction 2023

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings. The 2023 version sets high standards for ecological, economic, socio-cultural, and functional aspects throughout the entire life cycle of a building.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 03.05.2024 (3rd edition)	not applicable		Not relevant for assessment

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact, 29.05.2025 (4th edition)	not applicable		Not relevant for assessment



Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**



## **DGNB New Construction 2018**

The DGNB System (German Sustainable Building Council) assesses the sustainability of various types of buildings. It can be applied to both large-scale private and commercial projects as well as smaller residential buildings.

Criteria	No. / Relevant building components / construction materials / surfaces	Considered substances / aspects	Quality level
ENV 1.2 Local environmental impact	not applicable	not applicable	Not relevant for assessment

Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**



## Product labels

In the construction industry, high-quality materials are crucial for a building's indoor air quality and sustainability. Product labels and certificates offer guidance to meet these requirements. However, the evaluation criteria of these labels vary, and it is important to carefully assess them to ensure products align with the specific needs of a construction project.



Products bearing the Sentinel Holding Institute QNG-ready seal are suitable for projects aiming to achieve the "Qualitätssiegel Nachhaltiges Gebäude" (Quality Seal for Sustainable Buildings). QNG-ready products meet the requirements of QNG Appendix Document 3.1.3, "Avoidance of Harmful Substances in Building Materials." The KfW loan program Climate-Friendly New Construction with QNG may allow for additional funding.

Product:

**tesamoll® Premium Flexible, transparent**

SHI Product Passport no.:

**14884-10-1027**



## Legal notices

(\*) These criteria apply to the construction project as a whole. While individual products can positively contribute to the overall building score through proper planning, the evaluation is always conducted at the building level. The information was provided entirely by the manufacturer.

---

Find our criteria here: <https://www.sentinel-holding.eu/de/Themenwelten/Pr%C3%BCfkriterien%20f%C3%BCr%20Produkte>

---

The SHI Database is the first and only database for construction products whose comprehensive processes and data accuracy are regularly verified by the independent auditing company SGS-TÜV Saar



## Publisher

Sentinel Holding Institut GmbH  
Bötzinger Str. 38  
79111 Freiburg im Breisgau  
Germany  
Tel.: +49 761 590 481-70  
info@sentinel-holding.eu  
www.sentinel-holding.eu



# tesamoll® STANDARD I-Profile

## Product Information

BNR 5559

### Product Description

tesamoll® Standard I-Profile is a universal wind and draught stopper tape that is ideal for insulating doors & windows by sealing gaps between 1 and 3.5 mm.

### Product Features

- Self-adhesive, long-lasting foam profile
- Seals all gaps from 1 to 3.5mm
- Durability: 4 years
- Soft and flexible
- Wipe-clean

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PE	• Gap coverage	1 - 3.5 mm
• Type of adhesive	synthetic rubber		

### Properties/Performance Values

• Chemical resistance	no	• Residue free removal	no
• Durability	4 years	• Solvent free	yes
• Humidity resistance	no	• Temperature resistance	yes

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05559>



# tesamoll® P-Profile

## Product Information

BNR 5390, 5391, 5395, 55703

### Product Description

tesamoll® P-Profile is a self-adhesive window seal made for insulating windows. It is a durable wind stopper able to seal even larger gaps in older windows.

### Product Features

- Saves up to 35% of energy costs
- Self-adhesive, long-lasting rubber P-Profile
- Seals all gaps from 2 to 5mm
- Durability: 8 years
- Weather-, UV- and ozone-resistant
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Easy to remove
- Temperature-resistant from -50°C to +60°C

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	EPDM rubber foam	• Energy saving potential up to	35 %
• Type of adhesive	synthetic rubber	• Gap coverage up to	5 mm

### Properties/Performance Values

• Temperature resistance	yes	• Material	Fabric, Synthetic
• Chemical resistance	no	• Residue free removal	no
• Durability	8 years	• Solvent free	yes
• Humidity resistance	yes		



# tesamoll® P-Profile

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=05390>



# tesamoll® E-Profile

## Product Information

BNR 5361, 5362, 5445, 5463, 5464, 5491, 55701

### Product Description

The tesamoll® E-Profile is a self-adhesive and durable DIY rubber sealing tape. It is a flexible draught seal able to reduce your heating costs by up to 20%.

### Product Features

- Saves up to 20% of energy costs
- Self-adhesive high quality rubber E-Profile
- Seals all gaps from 1 to 3.5mm
- Durability: 8 years
- Weather-, UV- and ozone-resistant
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Easy to remove
- Temperature-resistant from -50°C to +60°C

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	EPDM rubber foam	• Energy saving potential up to	20 %
• Type of adhesive	synthetic rubber	• Gap coverage	1 - 3.5 mm

### Properties/Performance Values

• Chemical resistance	no	• Solvent free	yes
• Durability	8 years	• Temperature resistance	yes
• Residue free removal	no		



# tesamoll® E-Profile

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05361>



# tesamoll® STANDARD Door Brush

## Product Information

BNR 5433, 5433

### Product Description

tesamoll® STANDARD Door-to-floor Brush is a highly effective self-adhesive draught excluder brush. It keeps cold air out and is able to seal gaps up to 12 mm.

### Product Features

- Suitable for smooth floor surfaces like parquet and wooden floors, PVC, laminate
- For gaps of up to 12mm
- Easy self-adhesive fitting without screws or nails
- Durability: 4 years
- UV-resistant
- Abrasion-resistant
- Long-lasting and durable
- Material: plastic

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Type of adhesive	acrylic	• Gap coverage	12 mm
--------------------	---------	----------------	-------

### Properties/Performance Values

• Chemical resistance	no	• Residue free removal	no
• Durability	4 years	• Solvent free	yes
• Material	Plastic		



# tesamoll® STANDARD Door Brush

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=05433>



# tesamoll® Premium Flexible Transparent

## Product Information

BNR 5417, 5450

### Product Description

tesamoll® Premium Flexible is a highly effective and durable silicone sealing tape able to reliably seal even large gaps of typical of older doors and windows.

### Product Features

- Saves up to 40% of energy costs
- Self-adhesive, long-lasting Silicone Profile
- Durability: 15 years
- Extremely weather-, UV- and ozone-resistant
- One size fits all gap sizes from 1 to 7mm
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Temperature-resistant from -50° to +60°C

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	Fabric	• Energy saving potential up to	40 %
• Type of adhesive	synthetic rubber	• Gap coverage up to	7 mm

### Properties/Performance Values

• Temperature resistance	yes	• Material	Silicone, Fabric
• Chemical resistance	no	• Residue free removal	no
• Durability	15 years	• Solvent free	yes

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.